



KILREMSSKIVOR FÖR KONISK KLÄMBUSSNING

V-BELT PULLEYS FOR TAPER BUSH


Profil B/SPB/5V
Profile B/SPB/5V




Utf. / Type 1




Utf. / Type 2




Utf. / Type 3




Utf. / Type 4



Utf. / Type 6



Utf. / Type 7



Utf. / Type 8

Do	Ant. spår Grooves	Buss. Nr. Bush No.	Best. Nr. Code	Max A-hål Max bore	Typ	B	J	K	L	M	N	Vikt Weight
100	1	1610	1SPB100	42	1	25	-	-	25	-	-	0.9
	2	1610	2SPB100	42	3	44	62	19.0	25	-	-	1.2
	3	1610	3SPB100	42	3	63	62	38.0	25	-	-	1.7
112	1	1610	1SPB112	42	1	25	-	-	25	-	-	1.1
	2	1610	2SPB112	42	3	44	75	19.0	25	-	-	1.5
	3	1610	3SPB112	42	3	63	75	38.0	25	-	-	2.0
118	1	1610	1SPB118	42	1	25	-	-	25	-	92	1.3
	2	1610	2SPB118	42	3	44	81	19.0	25	-	-	1.7
	3	1610	3SPB118	42	3	63	81	38.0	25	-	-	2.3
125	1	1610	1SPB125	42	1	25	-	-	25	-	92	1.5
	2	2012	2SPB125	50	2	44	85	-	32	12.0	-	1.9
	3	2012	3SPB125	50	2	63	85	-	32	31.0	-	2.4
	4	2012	4SPB125	50	4	82	85	25.0	32	25.0	-	3.0
	5	2012	5SPB125	50	3	101	85	69.0	32	-	-	3.5
132	1	1610	1SPB132	42	1	25	-	-	25	-	92	1.8
	2	2012	2SPB132	50	2	44	92	-	32	12.0	-	2.2
	3	2012	3SPB132	50	2	63	92	-	32	31.0	-	2.8
	4	2012	4SPB132	50	4	82	92	25.0	32	25.0	-	3.4
	5	2012	5SPB132	50	4	101	92	34.5	32	34.5	-	3.7
140	1	1610	1SPB140	42	1	25	-	-	25	-	92	2.3
	2	2012	2SPB140	50	2	44	100	-	32	12.0	-	2.7
	3	2012	3SPB140	50	2	63	100	-	32	31.0	-	3.3
	4	2517	4SPB140	65	2	82	100	-	45	37.0	-	3.7
	5	2517	5SPB140	65	2	101	100	-	45	56.0	-	4.5
	6	2517	6SPB140	65	4	120	100	37.5	45	37.5	-	4.6
150	1	1610	1SPB150	42	1	25	-	-	25	-	92	2.7
	2	2012	2SPB150	50	2	44	110	-	32	12.0	-	3.1
	3	2517	3SPB150	65	2	63	110	-	45	18.0	-	3.9
	4	2517	4SPB150	65	2	82	110	-	45	37.0	-	4.4
	5	2517	5SPB150	65	4	101	110	28.0	45	28.0	-	5.2
	6	2517	6SPB150	65	4	120	110	37.5	45	37.5	-	5.6
160	1	1610	1SPB160	42	1	25	-	-	25	-	92	2.9
	2	2012	2SPB160	50	2	44	114	-	32	12.0	-	3.3
	3	2517	3SPB160	65	2	63	114	-	45	18.0	-	4.9
	4	2517	4SPB160	65	4	82	114	18.5	45	18.5	-	4.9
	5	2517	5SPB160	65	4	101	114	28.0	45	28.0	-	6.0
	6	3020	6SPB160	75	4	120	114	34.5	51	34.5	-	5.4
170	1	1610	1SPB170	42	1	25	-	-	25	-	92	2.9
	2	2012	2SPB170	50	2	44	124	-	32	12.0	-	3.3
	3	2517	3SPB170	65	2	63	124	-	45	18.0	-	4.9
	4	2517	4SPB170	65	4	82	124	18.5	45	18.5	-	5.7
	5	3020	5SPB170	75	4	101	124	25.0	51	25.0	-	6.1
	6	3020	6SPB170	75	4	120	124	34.5	51	34.5	-	6.5
	8	3020	8SPB170	75	4	158	129	53.5	51	53.5	-	8.0
180	1	1610	1SPB180	42	1	25	-	-	25	-	92	4.1
	2	2517	2SPB180	65	1	44	134	-	45	1.0	-	4.5
	3	2517	3SPB180	65	2	63	134	-	45	18.0	-	5.5
	4	2517	4SPB180	65	4	82	134	18.5	45	18.5	-	6.9
	5	3020	5SPB180	75	4	101	134	25.0	51	25.0	-	7.1
	6	3020	6SPB180	75	4	120	134	34.5	51	34.5	-	7.7
	8	3020	8SPB180	75	4	158	139	53.5	51	53.5	-	9.5
190	1	2012	1SPB190	50	1	25	-	-	32	7.0	112	4.6
	2	2517	2SPB190	65	1	44	-	-	45	1.0	124	5.0
	3	2517	3SPB190	65	2	63	144	-	45	18.0	-	6.3
	4	2517	4SPB190	65	4	82	144	18.5	45	18.5	-	7.6
	5	3020	5SPB190	75	4	101	144	25.0	51	25.0	-	8.1
	6	3020	6SPB190	75	4	120	144	34.5	51	34.5	-	9.2
	8	3020	8SPB190	75	4	158	149	53.5	51	53.5	-	11.2

Do	Ant. spår Grooves	Buss. Nr. Bush No.	Best. Nr. Code	Max A-hål Max bore	Typ	B	J	K	L	M	N	Vikt Weight
200	1	2012	1SPB200	50	1	25	-	-	32	7.0	95	5.0
	2	2517	2SPB200	65	1	44	-	-	45	1.0	124	5.4
	3	2517	3SPB200	65	2	63	154.0	-	45	18.0	-	6.5
	4	3020	4SPB200	75	2	82	154.0	-	51	31.0	-	8.8
	5	3020	5SPB200	75	2	101	154.0	-	51	50.0	-	9.1
	6	3020	6SPB200	75	4	120	154.0	34.5	51	34.5	-	10.3
	8	3535	8SPB200	90	4	158	159.0	34.5	89	34.5	-	13.5
212	1	2012	1SPB212	50	1	25	-	-	32	7.0	95	4.2
	2	2517	2SPB212	65	1	44	-	-	45	1.0	124	4.9
	3	2517	3SPB212	65	2	63	166.5	-	45	18.0	-	6.0
	4	3020	4SPB212	75	2	82	166.5	-	51	31.0	-	9.8
	5	3020	5SPB212	75	2	101	166.5	-	51	50.0	-	11.0
	6	3535	6SPB212	90	4	120	166.5	15.5	89	15.5	-	14.3
	8	3535	8SPB212	90	4	158	171.0	34.5	89	34.5	-	16.6
224	1	2012	1SPB224	50	1	25	-	-	32	7.0	95	4.7
	2	2517	2SPB224	65	1	44	-	-	45	1.0	124	5.3
	3	2517	3SPB224	65	2	63	178.0	-	45	18.0	-	6.3
	4	3020	4SPB224	75	2	82	178.0	-	51	31.0	-	11.3
	5	3020	5SPB224	75	2	101	178.0	-	51	50.0	-	12.7
	6	3535	6SPB224	90	4	120	178.0	15.5	89	15.5	-	17.0
	8	3535	8SPB224	90	4	158	184.0	34.5	89	34.5	-	19.3
	10	3535	10SPB224	90	4	196	184.0	46.0	89	61.0	-	21.8
236	1	2012	1SPB236	50	1	25	198.0	-	32	7.0	95	5.0
	2	2517	2SPB236	65	1	44	198.0	-	45	1.0	124	5.5
	3	2517	3SPB236	65	8	63	198.0	-	45	18.0	-	7.0
	4	3020	4SPB236	75	8	82	198.0	15.5	51	15.5	-	14.5
	5	3535	5SPB236	90	3	101	198.0	-	89	12.0	-	16.9
	6	3535	6SPB236	90	4	120	198.0	15.5	89	15.5	-	20.0
	8	3535	8SPB236	90	4	158	198.0	34.5	89	34.5	-	22.3
	10	3535	10SPB236	90	4	196	198.0	53.5	89	53.5	-	25.3
250	1	2012	1SPB250	50	1	25	212.0	-	32	7.0	95	5.4
	2	2517	2SPB250	65	7	44	-	-	45	1.0	124	5.5
	3	3020	3SPB250	75	2	63	204.0	-	51	12.0	-	7.7
	4	3020	4SPB250	75	2	82	204.0	-	51	31.0	-	19.6
	5	3535	5SPB250	90	2	101	204.0	-	89	12.0	-	21.7
	6	3535	6SPB250	90	4	120	204.0	15.5	89	15.5	-	23.3
	8	3535	8SPB250	90	4	158	204.0	34.5	89	34.5	-	27.5
	10	3535	10SPB250	90	4	196	204.0	46.0	89	61.0	-	29.3
265	2	2517	2SPB265	65	7	44	224.0	0.5	45	0.5	124	6.2
	3	3020	3SPB265	75	6	63	224.0	6.0	51	6.0	159	8.5
	4	3020	4SPB265	75	6	82	224.0	15.5	51	15.5	159	9.5
	5	3525	5SPB265	90	6	101	224.0	18.0	65	18.0	178	17.0
	6	3525	6SPB265	90	6	120	224.0	27.5	65	27.5	178	16.7
	8	3525	8SPB265	90	6	158	224.0	46.5	65	46.5	178	24.0
280	1	2012	1SPB280	50	7	25	242.0	-	32	7.0	95	6.1
	2	2517	2SPB280	65	7	44	242.0	0.5	45	0.5	124	6.8
	3	3020	3SPB280	75	8	63	242.0	6.0	51	6.0	159	8.6
	4	3020	4SPB280	75	6	82	242.0	15.5	51	15.5	159	10.1
	5	3535	5SPB280	90	6	101	239.0	6.0	89	6.0	178	17.8
	6	3535	6SPB280	90	6	120	239.0	15.5	89	15.5	178	19.6
	8	3535	8SPB280	90	6	158	239.0	34.5	89	34.5	-	26.7
	10	3535	10SPB280	90	6	196	239.0	46.0	89	61.0	-	30.5
300	1	2012	1SPB300	50	7	25	262.0	-				