



KILREMSSKIVOR FÖR KONISK KLÄMBUSSNING

V-BELT PULLEYS FOR TAPER BUSH


Profil B/SPB/5V
Profile B/SPB/5V




Utf. / Type 5



Utf. / Type 6



Utf. / Type 7



Utf. / Type 8

Do	Ant. spår Grooves	Buss. Nr. Bush No.	Best. Nr. Code	Max A-hål Max bore	Typ Type	B	J	K	L	M	N	Vikt Weight	
315	1	2012	1SPB315	50	7	25	277	-	32	7.0	95	7.2	
	2	2517	2SPB315	65	7	44	269	0.5	45	0.5	124	7.8	
	3	3020	3SPB315	75	8	63	269	6.0	51	6.0	159	9.6	
	4	3535	4SPB315	90	5	82	269	3.5	89	3.5	178	17.1	
	5	3535	5SPB315	90	6	101	269	6.0	89	6.0	178	18.8	
	6	3535	6SPB315	90	6	120	269	15.5	89	15.5	178	23.0	
	8	3535	8SPB315	90	6	158	274	34.5	89	34.5	178	26.0	
	10	3535	10SPB315	90	6	196	274	53.5	89	53.5	178	31.5	
	335	2	2517	2SPB335	65	7	44	297	-	45	1.0	120	7.8
		3	3020	3SPB335	75	8	63	297	6.0	51	6.0	145	10.5
4		3535	4SPB335	90	7	82	297	3.5	89	3.5	178	18.3	
5		3535	5SPB335	90	8	101	297	6.0	89	6.0	178	19.5	
6		3535	6SPB335	90	8	120	297	15.5	89	15.5	178	22.0	
8		3535	8SPB335	90	8	158	294	34.5	89	34.5	178	28.2	
10		4040	10SPB335	100	8	196	294	47.0	102	47.0	216	36.0	
355		2	3020	2SPB355	75	7	44	309	3.5	51	3.5	159	8.7
		3	3020	3SPB355	75	8	63	309	6.0	51	6.0	159	10.8
		4	3535	4SPB355	90	7	82	309	3.5	89	3.5	178	18.6
	5	3535	5SPB355	90	8	101	309	6.0	89	6.0	178	20.8	
	6	3535	6SPB355	90	6	120	309	15.5	89	15.5	178	22.8	
	8	3535	8SPB355	90	8	158	317	34.5	89	34.5	178	27.0	
	10	4040	10SPB355	100	8	196	317	47.0	102	47.0	216	38.0	
	375	2	3020	2SPB375	75	7	44	335	3.5	51	3.5	159	9.5
		3	3020	3SPB375	75	8	63	335	6.0	51	6.0	159	11.5
		4	3525	4SPB375	90	8	82	335	8.5	65	8.5	178	16.5
5		3525	5SPB375	90	8	101	335	18.0	65	18.0	178	21.0	
6		3525	6SPB375	90	8	120	335	27.5	65	27.5	178	25.0	
8		3525	8SPB375	90	8	158	335	46.5	65	46.5	178	28.0	
400		2	3020	2SPB400	75	7	44	354	3.5	51	3.5	159	10.0
		3	3535	3SPB400	90	7	63	354	13.0	89	13.0	178	18.3
	4	3535	4SPB400	90	7	82	354	3.5	89	3.5	178	20.5	
	5	3535	5SPB400	90	8	101	354	6.0	89	6.0	178	23.4	
	6	3535	6SPB400	90	8	120	354	15.5	89	15.5	178	25.1	
	8	4040	8SPB400	100	8	158	362	28.0	102	28.0	216	36.5	
	10	4040	10SPB400	100	8	196	362	47.0	102	47.0	216	41.0	
	425	2	3020	2SPB425	75	7	44	381	3.5	51	3.5	159	11.5
		3	3525	3SPB425	90	7	63	381	1.0	65	1.0	178	18.0
		4	3525	4SPB425	90	8	82	381	8.5	65	8.5	178	19.5
5		3525	5SPB425	90	8	101	381	18.0	65	18.0	178	23.0	
6		3525	6SPB425	90	8	120	381	27.5	65	27.5	178	25.1	
8		4030	8SPB425	100	8	158	381	34.5	89	34.5	216	35.1	
450		2	3020	2SPB450	75	7	44	410	3.5	51	3.5	159	12.1
		3	3535	3SPB450	90	7	63	410	13.0	89	13.0	178	21.9
	4	3535	4SPB450	90	7	82	410	3.5	89	3.5	178	24.5	
	5	3535	5SPB450	90	8	101	410	6.0	89	6.0	178	27.3	
	6	4040	6SPB450	100	8	120	410	9.0	102	9.0	216	35.5	
	8	4040	8SPB450	100	8	158	410	28.0	102	28.0	216	40.9	
	10	4545	10SPB450	110	8	196	410	40.5	115	40.5	242	53.5	
	475	2	3020	2SPB475	75	7	44	431	3.5	51	3.5	159	13.0
		3	3525	3SPB475	90	7	63	431	1.0	65	1.0	178	20.0
		4	3525	4SPB475	90	8	82	431	8.5	65	8.5	178	22.5
5		3525	5SPB475	90	8	101	431	18.0	65	18.0	178	26.5	
6		4030	6SPB475	100	8	120	431	15.5	89	15.5	216	33.5	
8		4030	8SPB475	100	8	158	431	34.5	89	34.5	216	39.5	

Do	Ant. spår Grooves	Buss. Nr. Bush No.	Best. Nr. Code	Max A-hål Max bore	Typ Type	B	J	K	L	M	N	Vikt Weight	
500	2	3020	2SPB500	75	7	44	454	3.5	51	3.5	159	13.2	
	3	3535	3SPB500	90	7	63	454	13.0	89	13.0	178	23.1	
	4	3535	4SPB500	90	7	82	454	3.5	89	3.5	178	26.6	
	5	3535	5SPB500	90	8	101	454	6.0	89	6.0	178	29.9	
	6	4040	6SPB500	100	8	120	454	9.0	102	9.0	216	38.9	
	8	4040	8SPB500	100	8	158	460	28.0	102	28.0	216	45.5	
	10	4545	10SPB500	110	8	196	460	40.5	115	40.5	242	61.0	
	530	2	3020	2SPB530	75	7	44	484	3.5	51	3.5	159	14.2
		3	3525	3SPB530	90	7	63	484	1.0	65	1.0	178	22.0
		4	3525	4SPB530	90	8	82	484	8.5	65	8.5	178	24.5
5		3525	5SPB530	90	8	101	484	18.0	65	18.0	178	28.0	
6		4030	6SPB530	100	8	120	484	15.5	89	15.5	216	35.5	
8		4030	8SPB530	100	8	158	484	34.5	89	34.5	216	42.0	
560		2	3020	2SPB560	75	7	44	525	3.5	51	3.5	159	16.5
		3	3535	3SPB560	90	7	63	525	-	89	26.0	178	25.9
	4	3535	4SPB560	90	7	82	525	-	89	7.0	178	29.0	
	5	4040	5SPB560	100	7	101	525	0.5	102	0.5	216	35.3	
	6	4040	6SPB560	100	8	120	525	9.0	102	9.0	216	43.1	
	8	4545	8SPB560	110	8	158	525	21.5	115	21.5	242	49.0	
	630	2	3020	2SPB630	75	7	44	584	3.5	51	3.5	146	18.5
		3	3535	3SPB630	90	7	63	584	13.0	89	13.0	178	28.9
4		3535	4SPB630	90	7	82	584	3.5	89	3.5	178	33.3	
5		4040	5SPB630	100	7	101	584	0.5	102	0.5	216	43.1	
6		4040	6SPB630	100	8	120	584	9.0	102	9.0	216	49.2	
8		4545	8SPB630	110	8	158	590	21.5	115	21.5	242	62.0	
10		4545	10SPB630	110	8	196	590	40.5	115	40.5	242	72.0	
710		2	3030	2SPB710	75	7	44	670	16.0	76	16.0	145	23.0
		3	3535	3SPB710	90	7	63	670	13.0	89	13.0	180	33.2
		4	3535	4SPB710	90	7	82	670	3.5	89	3.5	180	36.4
	5	4040	5SPB710	100	7	101	670	0.5	102	0.5	215	50.2	
	6	4545	6SPB710	110	8	120	670	2.5	115	2.5	242	62.3	
	8	4545	8SPB710	110	8	158	670	21.5	115	21.5	242	71.0	
	10	4545	10SPB710	110	8	196	670	40.5	115	40.5	242	80.0	
	800	2	3535	2SPB800	90	7	44	760	22.5	89	22.5	180	29.8
		3	3535	3SPB800	90	7	63	760	13.0	89	13.0	180	36.7
		4	4040	4SPB800	100	7	82	760	10.0	102	10.0	216	48.8
5		4040	5SPB800	100	7	101	760	0.5	102	0.5	216	56.1	
6		4545	6SPB800	110	8	120	760	2.5	115	2.5	242	71.4	
8		4545	8SPB800	110	8	158	760	21.5	115	21.5	242	90.9	
10		4545	10SPB800	110	8	196	760	40.5	115	40.5	242	102.0	
900		3	3535	3SPB900	90	7	63	858	13.0	89	13.0	180	46.8
		4	4040	4SPB900	100	7	82	858	3.0	76	3.0	216	55.0
		5	4545	5SPB900	110	7	101	858	7.0	115	7.0	242	74.8
	6	4545	6SPB900	110	8	120	858	2.5	115	2.5	242	81.5	
	8	4545	8SPB900	110	8	158	858	21.5	115	21.5	242	110.0	
	10	5050	10SPB900	125	8	196	858	34.5	127	34.5	267	126.0	
	1000	3	4040	3SPB1000	100	7	63	958	19.5	102	19.5	216	56.5
		4	4040	4SPB1000	100	7	82	958	10.0	102	10.0	216	66.5
		5	4545	5SPB1000	110	7	101	958	7.0	115	7.0	242	80.5
		6	4545	6SPB1000	110	8	120	958	2.5	115	2.5	242	90.0
8		5050	8SPB1000	125	8	158	958	15.5	127	15.5	267	132.0	
10		5050	10SPB1000	125	8	196	958	34.5	127	34.5	267	147.0	
1250		3	4040	3SPB1250	100	7	63	1208	19.5	102	19.5	216	120.0
		4	4545	4SPB1250	110	7	82	1208	16.5	115	16.5	242	152.0
		5	4545	5SPB1250	110	7	101	1208	7.0	115	7.0	242	175.0
		6	5050	6SPB1250	125	7	120	1208	3.5	127	3.5	267	190.0