


KILREMSSKIVOR FÖR KONISK KLÄMBUSSNING

V-BELT PULLEYS FOR TAPER BUSH


Profil C/SPC
Profile C/SPC




Utf. / Type 1




Utf. / Type 4




Utf. / Type 5



Utf. / Type 6



Utf. / Type 7



Utf. / Type 8

Do	Ant. spår	Buss. Nr.	Best. Nr.	Max A-hål	Typ	B	J	K	L	M	N	Vikt
	Grooves	Bush No.	Code	Max bore	Type							Weight
200	3	2517	3SPC200	65	4	85.0	151	20.0	45	20.0	-	9.0
	4	3020	4SPC200	75	4	110.5	151	29.8	51	29.8	-	10.5
	5	3535	5SPC200	90	4	136.0	151	16.0	89	31.0	-	14.0
	6	3535	6SPC200	90	4	161.5	151	15.8	89	56.8	-	17.0
	8	3535	8SPC200	90	4	212.5	151	45.8	89	77.8	-	23.0
212	3	3020	3SPC212	75	4	85.0	163	17.0	51	17.0	-	10.0
	4	3020	4SPC212	75	4	110.5	163	29.8	51	29.8	-	12.5
	5	3535	5SPC212	90	4	136.0	163	16.0	89	31.0	-	15.0
	6	3535	6SPC212	90	4	161.5	163	36.3	89	36.3	-	18.0
	8	3535	8SPC212	90	4	212.5	163	45.8	89	77.8	-	24.0
224	2	3020	2SPC224	75	4	59.5	170	4.3	51	4.3	-	8.1
	3	3020	3SPC224	75	4	85.0	170	17.0	51	17.0	-	11.0
	4	3535	4SPC224	90	4	110.5	170	10.8	89	10.8	-	14.0
	5	3535	5SPC224	90	4	136.0	170	23.5	89	23.5	-	16.2
	6	3535	6SPC224	90	4	161.5	170	36.3	89	36.3	-	19.0
	8	3535	8SPC224	90	4	212.5	170	45.8	89	77.8	-	24.9
236	3	3020	3SPC236	75	4	85.0	182	17.0	51	17.0	-	12.0
	4	3535	4SPC236	90	4	110.5	182	10.8	89	10.8	-	17.2
	5	3535	5SPC236	90	4	136.0	182	23.5	89	23.5	-	19.1
	6	3535	6SPC236	90	4	161.5	182	36.3	89	36.3	-	20.8
	8	3535	8SPC236	90	4	212.5	182	45.8	89	77.8	-	25.5
250	2	3020	2SPC250	75	4	59.5	170	4.1	51	4.5	-	9.8
	3	3020	3SPC250	75	4	85.0	200	17.0	51	17.0	-	14.5
	4	3535	4SPC250	90	4	110.5	200	10.8	89	10.8	-	20.7
	5	3535	5SPC250	90	4	136.0	200	23.5	89	23.5	-	22.8
	6	3535	6SPC250	90	4	161.5	200	36.3	89	36.3	-	26.0
	8	3535	8SPC250	90	4	212.5	200	61.8	89	61.8	-	29.7
265	3	3535	3SPC265	90	1	85.0	215	-	89	4.0	178	21.2
	4	3535	4SPC265	90	6	110.5	215	10.8	89	10.8	178	24.0
	5	3535	5SPC265	90	6	136.0	215	23.5	89	23.5	178	26.2
	6	3535	6SPC265	90	6	161.5	215	36.3	89	36.3	178	29.0
	8	3535	8SPC265	90	6	212.5	215	61.8	89	61.8	178	33.3
280	3	3535	8SPC280	90	1	85.0	230	-	89	4.0	178	24.0
	4	3535	4SPC280	90	6	110.5	230	10.8	89	10.8	178	29.0
	5	3535	5SPC280	90	6	136.0	230	23.5	89	23.5	178	31.0
	6	3535	6SPC280	90	6	161.5	230	36.3	89	36.3	178	33.8
	8	3535	8SPC280	90	6	212.5	230	61.8	89	61.8	178	37.5
300	3	3535	3SPC300	90	5	85.0	250	2.0	89	2.0	178	21.0
	4	3535	4SPC300	90	6	110.5	250	10.8	89	10.8	178	25.0
	5	3535	5SPC300	90	6	136.0	250	23.5	89	23.5	178	28.5
	6	3535	6SPC300	90	6	161.5	250	36.3	89	36.3	178	29.0
	8	4040	8SPC300	100	4	212.5	250	55.3	102	55.3	-	46.5
315	3	3535	3SPC315	90	5	85.0	265	2.0	89	2.0	178	21.6
	4	3535	4SPC315	90	6	110.5	265	10.8	89	10.8	178	24.6
	5	3535	5SPC315	90	6	136.0	265	23.5	89	23.5	178	29.0
	6	3535	6SPC315	90	6	161.5	265	36.3	89	36.3	178	31.4
	8	4040	8SPC315	100	4	212.5	265	55.3	102	55.3	200	50.0
335	3	3535	3SPC335	90	5	85.0	282	2.0	89	2.0	178	22.5
	4	3535	4SPC335	90	6	110.5	282	10.8	89	10.8	178	26.5
	5	3535	5SPC335	90	6	136.0	282	23.5	89	23.5	178	30.0
	6	3535	6SPC335	90	6	161.5	282	36.3	89	36.3	178	35.0
	8	4040	8SPC335	100	6	212.5	282	55.3	102	55.3	200	58.0
355	3	3535	3SPC355	90	5	85.0	305	2.0	89	2.0	178	22.9
	4	3535	4SPC355	90	6	110.5	305	10.8	89	10.8	178	28.3
	5	3535	5SPC355	90	6	136.0	305	23.5	89	23.5	178	32.5
	6	3535	6SPC355	90	6	161.5	305	36.3	89	36.3	178	36.0
	8	4040	8SPC355	100	6	212.5	305	55.3	102	55.3	200	67.5
375	3	3535	3SPC375	90	5	85.0	322	2.0	89	2.0	178	23.8
	4	3535	4SPC375	90	6	110.5	322	10.8	89	10.8	178	30.0
	5	3535	5SPC375	90	6	136.0	322	23.5	89	23.5	178	33.0
	6	4040	6SPC375	100	6	161.5	322	29.8	102	29.8	216	45.5
	8	4545	8SPC375	110	6	212.5	322	48.8	115	48.8	225	68.0
400	3	3535	4SPC400	90	7	85.0	350	2.0	89	2.0	178	24.1
	4	3535	4SPC400	90	8	110.5	350	10.8	89	10.8	178	28.0
	5	3535	5SPC400	90	8	136.0	350	23.5	89	23.5	178	34.0
	6	4040	6SPC400	100	6	161.5	350	29.8	102	29.8	216	48.0
	8	4545	8SPC400	110	6	212.5	350	48.8	115	48.8	240	65.0

Do	Ant. spår	Buss. Nr.	Best. Nr.	Max A-hål	Typ	B	J	K	L	M	N	Vikt
	Grooves	Bush No.	Code	Max bore	Type							Weight
425	3	3535	3SPC425	90	7	85.0	372	2.0	89	2.0	178	26.0
	4	3535	4SPC425	90	8	110.5	372	10.8	89	10.8	178	31.0
	5	4040	5SPC425	100	6	136.0	372	17.0	102	17.0	216	45.0
	6	4545	6SPC425	110	6	161.5	372	23.3	115	23.3	242	58.0
	8	4545	8SPC425	110	6	212.5	372	42.8	115	42.8	242	74.0
450	3	3535	3SPC450	90	7	85.0	400	2.0	89	2.0	178	28.6
	4	3535	4SPC450	90	8	110.5	400	10.8	89	10.8	178	33.5
	5	4040	5SPC450	100	8	136.0	400	17.0	102	17.0	216	45.0
	6	4545	6SPC450	110	6	161.5	400	23.3	115	23.3	242	61.1
	8	5050	8SPC450	125	6	212.5	400	42.8	127	42.8	265	78.7
475	3	3535	3SPC475	90	7	85.0	422	2.0	89	2.0	178	40.0
	4	3535	4SPC475	90	8	110.5	422	10.8	89	10.8	178	47.0
	5	4040	5SPC475	100	8	136.0	422	17.0	102	17.0	216	47.2
	6	4545	6SPC475	110	6	161.5	422	23.3	115	23.3	242	62.8
	8	5050	8SPC475	125	6	212.5	422	42.8	127	42.8	265	81.5
500	3	3535	3SPC500	90	7	85.0	450	2.0	89	2.0	178	30.9
	4	3535	4SPC500	90	8	110.5	450	10.8	89	10.8	178	39.0
	5	4040	5SPC500	100	8	136.0	450	17.0	102	17.0	216	48.7
	6	4545	6SPC500	110	8	161.5	450	23.3	115	23.3	242	60.2
	8	5050	8SPC500	125	6	212.5	450	42.8	127	42.8	265	87.4
530	3	3535	3SPC530	90	7	85.0	480	2.0	89	2.0	178	35.0
	4	4040	4SPC530	100	8	110.5	480	4.3	102	4.3	216	40.0
	5	4545	5SPC530	110	8	136.0	480	11.0	115	11.0	242	60.0
	6	5050	6SPC530	125	8	161.5	480	17.3	127	17.3	265	73.0
	8	5050	8SPC530	125	6	212.5	480	42.8	127	42.8	265	94.0
560	3	3535	3SPC560	90	7	85.0	510	2.0	89	2.0	178	36.0
	4	4040	4SPC560	100	8	110.5	510	4.3	102	4.3	216	50.0
	5	4545	5SPC560	110	8	136.0	510	11.0	115	11.0	242	63.0
	6	5050	6SPC560	125	8	161.5	510	17.3	127	17.3	265	77.0
	8	5050	8SPC560	125	8	212.5	510	42.8	127	42.8	265	94.0
630	3	4040	3SPC630	100	7	85.0	580	8.5	102	8.5	216	48.5
	4	4545	4SPC630	110	7	110.5	580	2.2	115	2.2	242	61.0
	5	5050	5SPC630	125	8	136.0	580	4.5	127	4.5	267	77.0
	6	5050	6SPC630	125	8	161.5	580	17.3	127	17.3	267	86.0
	8	5050	8SPC630	125	8	212.5	580	42.8	127	42.8	265	105.5
710	3	4040	3SPC710	100								