

KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING L, H, XH

TIMING BELT PULLEYS FOR TAPER BUSH L, H, XH

H 100 - 1/2" (12.7 mm)

Utförande Version		Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R		
Material: Stål Material: Steele		16 H 100F	5F	1108	28	64.68	63.31	70.0	-	45	31.0	22.0	9.0		
		18 H 100F	5F	1210	35	72.77	71.39	79.5	-	52	31.0	25.0	6.0		
		19 H 100F	5F	1210	35	76.81	75.44	83.0	-	56	31.0	25.0	6.0		
		20 H 100F	5F	1210	35	80.55	79.48	87.0	-	60	31.0	25.0	6.0		
Material: Gjutjärn Material: Cast Iron	Med Flänsar With Flanges	21 H 100F	5F	1210	35	84.89	83.52	91.0	-	63	32.0	25.0	7.0		
		22 H 100F	5F	1210	35	88.94	87.56	94.0	-	67	32.0	25.0	7.0		
		23 H 100F	5F	1210	35	92.98	91.61	102.0	-	71	32.0	25.0	7.0		
		24 H 100F	5F	1610	42	97.02	95.65	102.0	-	75	32.0	25.0	7.0		
		25 H 100F	5F	1610	42	101.06	99.69	112.0	-	79	32.0	25.0	7.0		
		26 H 100F	5F	1610	42	105.11	103.73	112.0	-	83	32.0	25.0	7.0		
		27 H 100F	5F	1610	42	109.15	107.78	120.0	-	87	32.0	25.0	7.0		
		28 H 100F	5F	1610	42	113.19	111.82	120.0	-	91	32.0	25.0	7.0		
		30 H 100F	5F	1610	42	121.28	119.90	128.0	-	99	32.0	25.0	7.0		
		32 H 100F	5WF	1610	42	129.36	127.99	135.0	92	108	32.0	25.0	7.0		
		36 H 100F	5WF	1610	42	145.53	144.16	158.0	92	124	32.0	25.0	7.0		
		40 H 100F	5WF	1610	42	161.70	160.33	168.0	92	140	32.0	25.0	7.0		
		44 H 100F	3WF	2012	50	177.87	176.50	184.0	106	153	32.0	32.0	-		
		48 H 100F	3WF	2012	50	194.04	192.67	200.0	106	169	32.0	32.0	-		
		Material: Gjutjärn Material: Cast Iron	Utan Flänsar Without Flanges	60 H 100F	9A	2012	50	242.55	241.18	-	106	223	34.0	32.0	1.0
				72 H 100F	9A	2012	50	291.06	289.69	-	106	270	34.0	32.0	1.0
84 H 100F	9A			2012	50	339.57	338.20	-	106	318	34.0	32.0	1.0		
96 H 100F	7A			2517	60	388.08	386.71	-	119	366	34.0	45.0	5.5		
120 H 100F	7A			2517	60	485.10	483.73	-	119	462	34.0	45.0	5.5		

H 150 - 1/2" (12.7 mm)

Utförande Version		Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R		
Material: Stål Material: Steele		18 H 150F	5F	1210	35	72.77	71.39	79.5	-	53	45.0	25.0	20.0		
		19 H 150F	5F	1210	35	76.81	75.44	83.0	-	56	45.0	25.0	20.0		
		20 H 150F	5F	1210	35	80.55	79.48	87.0	-	60	45.0	25.0	20.0		
Material: Gjutjärn Material: Cast Iron	Med Flänsar With Flanges	21 H 150F	5F	1210	35	84.89	83.52	91.0	-	64	45.0	25.0	20.0		
		22 H 150F	5F	1210	35	88.94	87.56	94.0	-	68	45.0	25.0	20.0		
		23 H 150F	5F	1610	42	92.98	91.61	102.0	-	71	45.0	25.0	20.0		
		24 H 150F	5F	1610	42	97.02	95.65	102.0	-	74	45.0	25.0	20.0		
		25 H 150F	5F	1610	42	101.06	99.69	112.0	-	78	45.0	25.0	20.0		
		26 H 150F	5F	1610	42	105.11	103.73	112.0	-	82	45.0	25.0	20.0		
		27 H 150F	5F	1610	42	109.15	107.78	120.0	-	87	45.0	25.0	20.0		
		28 H 150F	5F	1610	42	113.19	111.82	120.0	-	91	45.0	25.0	20.0		
		30 H 150F	5F	1610	42	121.28	119.90	128.0	-	99	45.0	25.0	20.0		
		32 H 150F	5WF	1610	42	129.36	127.99	135.0	92	108	45.0	25.0	20.0		
		36 H 150F	5WF	1610	42	145.53	144.16	158.0	92	124	45.0	25.0	20.0		
		40 H 150F	5WF	1610	42	161.70	160.33	168.0	92	140	45.0	25.0	20.0		
		44 H 150F	5WF	2012	50	177.87	176.50	184.0	106	153	45.0	32.0	13.0		
		48 H 150F	5WF	2012	50	194.04	192.67	200.0	106	169	46.0	32.0	13.0		
		Material: Gjutjärn Material: Cast Iron	Utan Flänsar Without Flanges	60 H 150F	9A	2012	50	242.55	241.18	-	106	223	45.0	32.0	7.5
				72 H 150F	9A	2012	50	291.06	289.69	-	106	270	46.0	32.0	7.5
84 H 150F	9A			2012	50	339.57	338.20	-	106	320	46.0	32.0	7.5		
96 H 150F	9A			2517	60	388.08	386.71	-	119	366	46.0	45.0	0.5		
120 H 150F	9A			2517	60	485.10	483.73	-	119	462	46.0	45.0	0.5		