

KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING L, H, XH

TIMING BELT PULLEYS FOR TAPER BUSH L, H, XH

H 200 - 1/2" (12.7 mm)

| Utförande Version | | Best Nr. Code | Typ Type | Bussning Bush | Max. Axelhål Max. Bore | Dp | De | Df | Dm | Di | F | S | R |
|---|-----------------------------|---------------------------------|-------------|------------------|---------------------------|--------|--------|--------|-----|------|------|------|------|
| Material: Stål Material: Steele | | 18 H 200F | 5F | 1210 | 35 | 72.77 | 71.39 | 79.5 | - | 52 | 58.0 | 25.0 | 33.0 |
| | | 19 H 200F | 5F | 1210 | 35 | 76.81 | 75.44 | 83.0 | - | 56 | 58.0 | 25.0 | 33.0 |
| | | 20 H 200F | 5F | 1610 | 42 | 80.55 | 79.48 | 87.0 | - | 60 | 58.0 | 25.0 | 33.0 |
| Material: Gjutjärn Material: Cast Iron | Med Flänsar With Flanges | 21 H 200F | 5F | 1610 | 42 | 84.89 | 83.52 | 91.0 | - | 64 | 58.0 | 25.0 | 33.0 |
| | | 22 H 200F | 5F | 1610 | 42 | 88.94 | 87.56 | 94.0 | - | 68 | 58.0 | 25.0 | 33.0 |
| | | 23 H 200F | 5F | 1610 | 42 | 92.98 | 91.61 | 102.0 | - | 71 | 58.0 | 25.0 | 33.0 |
| | | 24 H 200F | 5F | 1610 | 42 | 97.02 | 95.65 | 102.0 | - | 74 | 58.0 | 25.0 | 33.0 |
| | | 25 H 200F | 5F | 1610 | 42 | 101.06 | 99.69 | 112.0 | - | 78 | 58.0 | 25.0 | 33.0 |
| | | 26 H 200F | 5F | 1610 | 42 | 105.11 | 103.73 | 112.0 | - | 82 | 58.0 | 25.0 | 33.0 |
| | | 27 H 200F | 5F | 1610 | 42 | 109.15 | 107.78 | 120.0 | - | 87 | 58.0 | 25.0 | 33.0 |
| | | 28 H 200F | 5F | 1610 | 42 | 113.19 | 111.82 | 120.0 | - | 91 | 58.0 | 25.0 | 33.0 |
| | | 30 H 200F | 5F | 1610 | 42 | 121.28 | 119.90 | 128.0 | - | 99 | 58.0 | 25.0 | 33.0 |
| | | 32 H 200F | 5F | 2012 | 50 | 129.36 | 127.99 | 135.0 | - | 107 | 58.0 | 32.0 | 26.0 |
| | | 36 H 200F | 5WF | 2012 | 50 | 145.53 | 144.16 | 158.0 | 102 | 124 | 58.0 | 32.0 | 26.0 |
| | | 40 H 200F | 5WF | 2012 | 50 | 161.70 | 160.33 | 168.0 | 106 | 140 | 58.0 | 32.0 | 26.0 |
| | | 44 H 200F | 5WF | 2012 | 50 | 177.87 | 176.50 | 184.0 | 106 | 153 | 58.0 | 32.0 | 26.0 |
| | | 48 H 200F | 5WF | 2517 | 60 | 194.04 | 192.67 | 200.0 | 119 | 169 | 58.0 | 45.0 | 13.0 |
| | | Utan Flänsar Without Flanges | 60 H 200F | 9A | 2517 | 60 | 242.55 | 241.18 | - | 119 | 223 | 60.0 | 45.0 |
| 72 H 200F | 9A | | 2517 | 60 | 291.06 | 289.69 | - | 119 | 270 | 60.0 | 45.0 | 7.5 | |
| 84 H 200F | 9A | | 2517 | 60 | 339.57 | 338.20 | - | 119 | 320 | 60.0 | 45.0 | 7.5 | |
| 96 H 200F | 9A | | 2517 | 60 | 388.08 | 386.71 | - | 119 | 366 | 60.0 | 45.0 | 7.5 | |
| 120 H 200F | 9A | | 2517 | 60 | 485.10 | 483.73 | - | 119 | 462 | 60.0 | 45.0 | 7.5 | |

H 300 - 1/2" (12.7 mm)

| Utförande Version | | Best Nr. Code | Typ Type | Bussning Bush | Max. Axelhål Max. Bore | Dp | De | Df | Dm | Di | F | S | R | |
|--|-----------------------------|---------------------------------|-------------|------------------|---------------------------|--------|--------|--------|-----|-----|------|------|------|------|
| Material: Stål Material: Steele | | 20 H 300F | 4F | 1615 | 42 | 80.85 | 79.48 | 87 | - | 65 | 84.0 | 38.0 | 23.0 | |
| | | 21 H 300F | 4F | 1615 | 42 | 84.89 | 83.52 | 91 | - | 66 | 84.0 | 38.0 | 23.0 | |
| Material: Gjutjärn Materiale: Cast Iron | Med Flänsar With Flanges | 22 H 300F | 4F | 1615 | 42 | 88.94 | 87.56 | 94 | - | 67 | 84.0 | 38.0 | 23.0 | |
| | | 23 H 300F | 4F | 1615 | 42 | 92.98 | 91.61 | 102 | - | 71 | 84.0 | 38.0 | 23.0 | |
| | | 24 H 300F | 4F | 1615 | 42 | 97.02 | 95.65 | 102 | - | 75 | 84.0 | 38.0 | 23.0 | |
| | | 25 H 300F | 4F | 1615 | 42 | 101.06 | 99.69 | 112 | - | 79 | 84.0 | 38.0 | 23.0 | |
| | | 26 H 300F | 4F | 1615 | 42 | 105.11 | 103.73 | 112 | - | 83 | 84.0 | 38.0 | 23.0 | |
| | | 27 H 300F | 4F | 2012 | 50 | 109.15 | 107.78 | 120 | - | 87 | 84.0 | 32.0 | 26.0 | |
| | | 28 H 300F | 4F | 2012 | 50 | 113.19 | 111.82 | 120 | - | 91 | 84.0 | 32.0 | 26.0 | |
| | | 30 H 300F | 4F | 2012 | 50 | 121.28 | 119.90 | 128 | - | 99 | 84.0 | 32.0 | 26.0 | |
| | | 32 H 300F | 4F | 2517 | 60 | 129.36 | 127.99 | 135 | - | 107 | 84.0 | 45.0 | 19.5 | |
| | | 36 H 300F | 4F | 2517 | 60 | 145.53 | 144.16 | 158 | - | 124 | 84.0 | 45.0 | 19.5 | |
| | | 40 H 300F | 4F | 2517 | 60 | 161.70 | 160.33 | 168 | - | 137 | 84.0 | 45.0 | 19.5 | |
| | | 44 H 300F | 4WF | 2517 | 60 | 177.87 | 176.50 | 184 | 119 | 153 | 86.0 | 45.0 | 20.5 | |
| | | 48 H 300F | 4WF | 2517 | 60 | 194.04 | 192.67 | 200 | 119 | 169 | 86.0 | 45.0 | 20.5 | |
| | | Utan Flänsar Without Flanges | 60 H 300F | 9A | 2517 | 60 | 242.55 | 241.18 | - | 119 | 223 | 86.0 | 45.0 | 20.5 |
| | | | 72 H 300F | 9A | 2517 | 60 | 291.06 | 289.69 | - | 119 | 270 | 86.0 | 45.0 | 20.5 |
| | | | 84 H 300F | 9A | 2517 | 60 | 339.57 | 338.20 | - | 119 | 320 | 86.0 | 45.0 | 20.5 |
| | | | 96 H 300F | 9A | 3030 | 75 | 388.08 | 386.71 | - | 150 | 362 | 86.0 | 76.0 | 5.0 |
| | | | 120 H 300F | 9A | 3030 | 75 | 485.10 | 483.73 | - | 150 | 460 | 86.0 | 76.0 | 5.0 |