


LÄNKLAGER

SPHERICAL PLAIN BEARINGS

Typ GL

Standard


Med yttering förzinkad samt återfettningsbar.
Lämplig för axiala laster.



Type GL

Standard

Spherical plain bearings with outer ring,
Zinc plated and regreasable.
Especially suited for axial loads.



Storlek Size	B	M	A	O	Statisk belast. Static load kN	Dynamisk belast. Dynamic load kN	Max varvtal Limiting speed rpm	Vikt Weight g
GL5	8	6.00	16	7.7	10.0	2.5	900	8
GL6	9	6.75	18	8.9	12.8	3.2	760	12
GL8	12	9.00	22	10.4	21.6	5.4	620	23
GL10	14	10.50	26	12.9	30.0	7.5	500	38
GL12	16	12.00	30	15.4	40.0	10.0	450	58
GL14	19	13.50	34	16.8	51.6	12.9	360	83
GL16	21	15.00	38	19.3	64.4	16.1	350	115
GL18	23	16.50	42	21.8	78.4	19.6	320	150
GL20	25	18.00	46	24.3	94.4	23.6	280	200
GL22	28	20.00	50	25.8	114.4	28.6	250	270
GL25	31	22.00	56	29.6	141.6	35.4	230	375

Material:

Yttering: Automatstål 9SMnPb28K förzinkat

Bussning: Mässing CuZn40Al1

Innering: Rullagerstål 100Cr6 härdad,
slipat samt polerat

Kan även levereras i tätat utförande.

Materials:

Outer ring: Free-cutting steel 9SMnPb28K zinc plated

Insert: Special brass CuZn40Al1

Ball: Bearing steel 100Cr6, hardened,
ground, polished

This series is also available sealed