

KUGGREMSHJUL FÖRBORRADE, HTD

TIMING BELT PULLEYS STANDARD, HTD

HTD 3M-06

Utförande Version	Best Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	F	L	d	
Material: Aluminium Materiale: Aluminium	Med Flänsar With Flanges	10-3M-6FB	1F	10	9.55	8.79	13.0	13.0	7.2	14.5	-
		12-3M-6FB	1F	12	11.46	10.70	15.0	15.0	7.2	14.5	-
		14-3M-6FB	1F	14	13.37	12.61	16.0	16.0	7.2	14.5	-
		15-3M-6FB	1F	15	14.32	13.56	17.5	17.5	7.2	14.5	-
		16-3M-6FB	6F	16	15.28	14.52	18.0	10.0	9.8	17.5	4
		18-3M-6FB	6F	18	17.19	16.43	20.0	11.0	9.8	17.5	6
		20-3M-6FB	6F	20	19.10	18.34	23.0	13.0	9.8	17.5	6
		21-3M-6FB	6F	21	20.05	19.29	25.0	14.0	9.8	17.5	6
		22-3M-6FB	6F	22	21.01	20.25	25.0	14.0	9.8	17.5	6
		24-3M-6FB	6F	24	22.92	22.16	25.0	14.0	9.8	17.5	6
		26-3M-6FB	6F	26	24.83	24.07	28.0	16.0	9.8	17.5	6
		28-3M-6FB	6F	28	26.74	25.98	32.0	18.0	9.8	17.5	6
		30-3M-6FB	6F	30	28.65	27.89	32.0	20.0	9.8	17.5	6
		32-3M-6FB	6F	32	30.56	29.80	37.0	22.0	9.8	17.5	6
	36-3M-6FB	6F	36	34.38	33.62	38.0	26.0	10.3	18.0	6	
	40-3M-6FB	6F	40	38.20	37.44	43.0	28.0	10.3	18.0	6	
	44-3M-6FB	6F	44	42.02	41.26	48.0	33.0	10.3	18.0	6	
	Utan Flänsar Without Flanges	48-3M-6FB	6	48	45.84	45.08	-	33.0	10.3	18.6	8
		60-3M-6FB	6	60	57.30	56.54	-	33.0	10.3	18.6	8
		72-3M-6FB	6	72	68.75	67.99	-	33.0	10.3	18.6	8

HTD 3M-09

Utförande Version	Best Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	F	L	d	
Material: Aluminium Materiale: Aluminium	Med Flänsar With Flanges	10-3M-9FB	1F	10	9.55	8.79	13.0	13	10.2	17.5	-
		12-3M-9FB	1F	12	11.46	10.70	15.0	15	10.2	17.5	-
		14-3M-9FB	1F	14	13.37	12.61	16.0	16	10.2	17.5	-
		15-3M-9FB	1F	15	14.32	13.56	17.5	17	10.2	17.5	-
		16-3M-9FB	6F	16	15.28	14.52	18.0	10	12.8	20.6	4
		18-3M-9FB	6F	18	17.19	16.43	20.0	11	12.8	20.6	6
		20-3M-9FB	6F	20	19.10	18.34	23.0	13	12.8	20.6	6
		21-3M-9FB	6F	21	20.05	19.29	25.0	14	12.8	20.6	6
		22-3M-9FB	6F	22	21.01	20.25	25.0	14	12.8	20.6	6
		24-3M-9FB	6F	24	22.92	22.16	25.0	14	12.8	20.6	6
		26-3M-9FB	6F	26	24.83	24.07	28.0	16	12.8	20.6	6
		28-3M-9FB	6F	28	26.74	25.98	32.0	18	12.8	20.6	6
		30-3M-9FB	6F	30	28.65	27.89	32.0	20	12.8	20.6	6
		32-3M-9FB	6F	32	30.56	29.80	37.0	22	12.8	20.6	6
	36-3M-9FB	6F	36	34.38	33.62	38.0	26	13.4	22.2	6	
	40-3M-9FB	6F	40	38.20	37.44	43.0	28	13.4	22.2	6	
	44-3M-9FB	6F	44	42.02	41.26	48.0	33	13.4	22.2	6	
	Utan Flänsar Without Flanges	48-3M-9FB	6	48	45.84	45.08	-	33	13.4	22.2	8
		60-3M-9FB	6	60	57.30	56.54	-	33	13.4	22.2	8
		72-3M-9FB	6	72	68.75	67.99	-	33	13.4	22.2	8