

# KUGGREMSHJUL FÖRBORRADE, HTD

## TIMING BELT PULLEYS STANDARD, HTD

### HTD 14M-40

Utförande Version		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	d
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-14M-40FB	6F	28	124.78	122.12	128	100	-	54	69	24
		29-14M-40FB	6F	29	129.23	126.57	142	100	-	54	69	24
		30-14M-40FB	6F	30	133.69	130.99	142	100	-	54	69	24
		32-14M-40FB	6F	32	142.60	139.88	158	100	-	54	69	24
		34-14M-40FB	6F	34	151.52	148.79	158	100	-	54	69	24
		36-14M-40FB	6F	36	160.43	157.68	168	100	-	54	69	24
		38-14M-40FB	6F	38	169.34	166.60	184	120	-	54	69	24
		40-14M-40FB	6F	40	178.25	175.49	192	120	-	54	69	24
		44-14M-40FB	6F	44	196.08	193.28	211	120	-	54	69	24
		48-14M-40FB	6WF	48	213.90	211.11	226	135	172	54	69	24
	Utan Flänsar Without Flanges	56-14M-40FB	6WF	56	249.55	246.76	265	135	207	54	69	28
		64-14M-40FB	6WF	64	285.21	282.41	296	135	242	54	69	28
		72-14M-40FB	6A	72	320.86	318.06	-	135	278	54	69	28
		80-14M-40FB	6A	80	356.51	353.71	-	135	314	54	69	28
		90-14M-40FB	6A	90	401.07	398.28	-	135	358	54	69	28
		112-14M-40FB	6A	112	499.11	496.32	-	135	456	54	69	28
		144-14M-40FB	6A	144	641.71	638.92	-	135	600	54	69	28
		168-14M-40FB	6A	168	748.66	745.87	-	135	706	54	69	28
		192-14M-40FB	6A	192	855.62	852.82	-	135	813	54	69	28
		216-14M-40FB	6A	216	962.57	959.76	-	150	920	54	69	28

### HTD 14M-55

Utförande Version		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	d
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-14M-55FB	6F	28	124.78	122.12	128	100	-	70	85	24
		29-14M-55FB	6F	29	129.23	126.57	142	100	-	70	85	24
		30-14M-55FB	6F	30	133.69	130.99	142	100	-	70	85	24
		32-14M-55FB	6F	32	142.60	139.88	158	100	-	70	85	24
		34-14M-55FB	6F	34	151.52	148.79	158	100	-	70	85	24
		36-14M-55FB	6F	36	160.43	157.68	168	100	-	70	85	24
		38-14M-55FB	6F	38	169.34	166.60	184	120	-	70	85	24
		40-14M-55FB	6F	40	178.25	175.49	192	120	-	70	58	24
		44-14M-55FB	6F	44	196.08	193.28	211	120	-	70	85	24
		48-14M-55FB	6F	48	213.90	211.11	226	135	172	70	70	24
	Utan Flänsar Without Flanges	56-14M-55FB	10WF	56	249.55	246.76	265	135	207	70	70	28
		64-14M-55FB	10WF	64	285.21	282.41	296	135	242	70	70	28
		72-14M-55FB	10A	72	320.86	318.06	-	135	278	70	70	28
		80-14M-55FB	10A	80	356.51	353.71	-	135	314	70	70	28
		90-14M-55FB	10A	90	401.07	398.28	-	135	358	70	70	28
		112-14M-55FB	10A	112	499.11	496.32	-	135	456	70	70	28
		144-14M-55FB	10A	144	641.71	638.92	-	135	600	70	70	28
		168-14M-55FB	10A	168	748.66	745.87	-	135	706	70	70	28
		192-14M-55FB	10A	192	855.62	852.82	-	135	813	70	70	28
		216-14M-55FB	10A	216	962.57	959.76	-	150	920	70	70	28