

# KUGGREMSHJUL FÖRBORRADE, HTD

## TIMING BELT PULLEYS STANDARD, HTD

### HTD 14M-170

Utförande Version		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	d
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-14M-170FB	6F	28	124.78	122.12	128	100	-	187	202	32
		29-14M-170FB	6F	29	129.23	126.57	142	100	-	187	202	32
		30-14M-170FB	6F	30	133.69	130.99	142	100	-	187	202	32
		32-14M-170FB	6F	32	142.60	139.88	158	100	-	187	202	32
		34-14M-170FB	6F	34	151.52	148.79	160	100	-	187	202	32
		36-14M-170FB	6F	36	160.43	157.68	168	120	-	187	202	32
		38-14M-170FB	6F	38	169.34	166.60	184	135	-	187	202	32
		40-14M-170FB	6F	40	178.25	175.49	192	135	-	187	202	32
		44-14M-170FB	6F	44	196.08	193.28	211	160	-	187	202	32
		48-14M-170FB	6F	48	213.90	211.11	226	160	-	187	202	32
		56-14M-170FB	6F	56	249.55	246.76	265	160	-	187	202	32
		64-14M-170FB	6F	64	285.21	282.41	296	180	-	187	202	32
	Utan Flänsar Without Flanges	72-14M-170FB	10W	72	320.86	318.06	-	180	278	187	187	32
		80-14M-170FB	10W	80	356.51	353.71	-	180	314	187	187	32
		90-14M-170FB	10A	90	401.07	398.28	-	180	358	187	187	38
		112-14M-170FB	10A	112	499.11	496.32	-	200	456	187	187	38
		144-14M-170FB	10A	144	641.71	638.92	-	220	600	187	187	38
		168-14M-170FB	10A	168	748.66	745.87	-	220	706	187	187	38
		192-14M-170FB	10A	192	855.62	852.82	-	220	813	187	187	38
		216-14M-170FB	10A	216	962.57	959.76	-	220	920	187	187	38

