

# MIAB-FIX SPÄNNFÖRBAND


## MIAB-FIX CLAMPING UNITS



### MIAB-FIX A

Ingen självcentrering  
Stort överförbart moment

Not self Centering  
Medium-high torques



### MIAB-FIX A

Best. ex. / Order ex. MIAB-FIX-A-d


d mm	D mm	B mm	L mm	M mm	Ts Nm	T Nm	F kN	P N/mm <sup>2</sup>
18	47	20	26	M 6	16	290	32	110
19	47	20	26	M 6	16	300	32	110
20	47	20	26	M 6	16	320	32	110
22	47	20	26	M 6	16	340	32	110
24	50	20	26	M 6	16	420	35	110
25	50	20	26	M 6	16	430	34	110
28	55	20	26	M 6	16	600	44	110
30	55	20	26	M 6	16	650	44	110
32	60	20	26	M 6	16	770	48	120
35	60	20	26	M 6	16	830	48	120
38	65	20	26	M 6	16	1100	56	140
40	65	20	26	M 6	16	1150	58	140
42	75	24	32	M 8	38	1800	86	150
45	75	24	32	M 8	38	2000	90	160
48	80	24	32	M 8	38	2100	90	150
50	80	24	32	M 8	38	2200	90	150
55	85	24	32	M 8	38	2900	100	160
60	90	24	32	M 8	38	3100	100	150
65	95	24	32	M 8	38	3600	110	150
70	110	28	38	M 10	75	5800	170	170
75	115	28	38	M 10	75	6200	170	160
80	120	28	38	M 10	75	6700	170	160
85	125	28	38	M 10	75	7700	180	160
90	130	28	38	M 10	75	8200	180	160
95	135	28	38	M 10	75	9800	200	160
100	145	30	42	M 12	130	12000	240	170
110	155	30	42	M 12	130	13000	240	160
120	165	30	42	M 12	130	16000	270	170
130	180	38	50	M 12	130	22000	340	150
140	190	38	50	M 12	130	26000	380	150
150	200	38	50	M 12	130	30000	400	160
160	210	38	50	M 12	130	35000	440	160
170	225	44	58	M 14	200	43000	500	160
180	235	44	58	M 14	200	50000	550	160
190	250	52	66	M 14	200	62000	620	150
200	260	52	66	M 14	200	69000	690	150
220	285	56	72	M 16	300	91000	920	150
240	305	56	72	M 16	300	115000	960	160
260	325	56	72	M 16	300	140000	1050	170
280	355	66	87	M 18	400	170000	1200	150
300	375	66	87	M 18	400	210000	1400	160
320	405	78	101	M 20	580	260000	1600	150
340	425	78	101	M 20	580	270000	1600	140
360	455	90	116	M 22	770	350000	1900	140
380	475	90	116	M 22	770	370000	1900	130
400	495	90	116	M 22	770	390000	1900	120

T<sub>s</sub> (Nm) Åtdragningsmoment per skruv. / Screws tightening torque

T<sub>n</sub> (Nm) Åtdragningsmoment för mutter. / Nut setting torque

T (Nm) Överförbart moment T alternativt axial kraft F med åtdragningsmomentet TS. Observera, endast 100% av T alt. F kan utnyttjas.  
F (kN) Torque or axial force transmissible with tightening torque TS.  
Only 100% of T or F can be used

p (N / mm<sup>2</sup>) Yttryck på nav. / Hub surface pressure



### MIAB-FIX SD

Utvändig klämkoppling, mycket god koncentricitet  
External clamping, excellent Concentricity

### MIAB-FIX SD

Best. ex. / Order ex. MIAB-FIX-SD-d

d mm	ds mm	D mm	L mm	B mm	H mm	C max	M mm	Ts Nm	T Nm	F kN	
16	12	41	19	15	11	0.017	M 5	4	50	9	
	13								70	10	
	14								90	13	
24	19	50	23	19	14	0.017	M 5	4	180	26	
									21	210	27
									24	250	29
30	25	60	25	21	16	0.017	M 5	4	310	26	
									26	340	27
									28	380	28
36	30	72	27	23	18	0.017	M 6	12	460	50	
									31	590	54
									32	630	58
44	35	80	29	25	20	0.032	M 6	12	630	65	
									36	780	74
									38	860	77
50	40	90	31	27	22	0.032	M 6	12	940	79	
									42	1100	85
									44	1300	90
55	45	100	34	30	23	0.032	M 6	12	1200	80	
									48	1500	90
									48	1900	100
62	50	110	34	30	23	0.032	M 6	12	1800	100	
									52	2200	110
									52	2400	120
68	55	115	34	30	23	0.038	M 6	12	2000	100	
									60	2500	110
									60	3100	120
75	60	138	38	33	25	0.048	M 8	30	2500	120	
									65	3200	140
									65	3900	150
80	65	145	38	32	25	0.048	M 8	30	3200	120	
									70	3900	140
									70	4600	160
90	70	155	45	39	30	0.048	M 8	30	4700	170	
									75	6000	190
									75	7200	210
100	75	170	49.5	44	34	0.048	M 8	30	6900	180	
									80	7500	220
									80	9000	240
110	80	185	57	50	39	0.048	M 10	59	7200	230	
									85	9000	250
									85	11000	260
115	85	188	57	50	39	0.048	M 10	59	8500	210	
									90	10000	240
									90	12000	270
125	90	215	61	54	42	0.056	M 10	59	11000	300	
									95	13000	320
									95	15000	350
130	90	215	59	52	42	0.056	M 10	59	13700	300	
									100	15800	330
									100	18200	360
140	95	230	68	60	46	0.056	M 12	100	15000	360	
									105	17000	400
									105	20000	420
155	105	263	70	62	50	0.069	M 12	100	20000	390	
									110	23000	420
									115	26000	450
165	115	290	78	68	56	0.069	M 16	250	36000	630	
									120	39000	660
									125	44000	700
175	125	300	78	68	56	0.079	M 16	250	40000	650	
									130	44000	680
									135	49000	720
185	135	330	96	86	71	0.079	M 16	250	55000	815	
									140	60000	875
									145	65000	896
195	140	350	96	86	71	0.079	M 16	250	66000	950	
									150	76000	1000
									155	82000	1100
220	160	370	114	104	88	0.079	M 16	250	95000	1200	
									165	102000	1300
									170	110000	1300
240	170	405	122	109	92	0.079	M 20	490	120000	1500	
									180	140000	1600
									190	160000	1700