

KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING, HTD

TIMING BELT PULLEYS FOR TAPER BUSH, HTD

HTD 8M-20

Utförande Version		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	24-8M-20F	5F	24	1108	25	61.12	59.75	67	-	42	28	22	6
		26-8M-20F	5F	26	1108	25	66.21	64.84	67	-	46	28	22	6
		28-8M-20F	5F	28	1108	25	71.30	70.08	75	-	50	28	22	6
		30-8M-20F	5F	30	1108	25	76.39	75.13	83	-	58	28	22	6
		32-8M-20F	5F	32	1610	42	81.49	80.16	87	-	62	28	25	3
		34-8M-20F	5F	34	1610	42	86.58	85.22	91	-	65	28	25	3
		36-8M-20F	5F	36	1610	42	91.67	90.30	97	-	68	28	25	3
		38-8M-20F	5F	38	1610	42	96.77	95.39	102	-	72	28	25	3
		40-8M-20F	5F	40	1610	42	101.86	100.49	112	-	76	28	25	3
		44-8M-20F	8F	44	2012	50	112.05	110.67	120	93	-	28	32	4
		48-8M-20F	8F	48	2012	50	122.23	120.86	128	96	-	28	32	4
		56-8M-20F	8F	56	2012	50	142.60	141.23	150	110	-	28	32	4
	64-8M-20F	8WF	64	2012	50	162.97	161.60	168	110	137	28	32	4	
	72-8M-20F	8WF	72	2012	50	183.35	181.97	192	110	158	28	32	4	
	80-8M-20F	8W	80	2012	50	203.72	202.35	-	110	180	28	32	4	
	Utan Flänsar Without Flanges	90-8M-20F	8A	90	2012	50	229.18	227.81	-	110	204	28	32	4

HTD 8M-30

Utförande Version		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	24-8M-30F	5F	24	1108	25	61.12	59.75	67	-	42	38	22	16
		26-8M-30F	5F	26	1108	25	66.21	64.84	67	-	46	38	22	16
		28-8M-30F	5F	28	1108	25	71.30	70.08	75	-	50	38	22	16
		30-8M-30F	3F	30	1615	42	76.39	75.13	83	-	-	38	38	-
		32-8M-30F	3F	32	1615	42	81.49	80.16	87	-	-	38	38	-
		34-8M-30F	3F	34	1615	42	86.58	85.22	91	-	-	38	38	-
		36-8M-30F	3F	36	1615	42	91.67	90.30	97	-	-	38	38	-
		38-8M-30F	3F	38	1615	42	96.77	95.39	102	-	-	38	38	-
		40-8M-30F	3F	40	1615	42	101.86	100.49	112	-	-	38	38	-
		44-8M-30F	4F	44	2012	50	112.05	110.67	120	-	91	38	32	3
		48-8M-30F	4F	48	2012	50	122.23	120.86	128	-	95	38	32	3
		56-8M-30F	4F	56	2012	50	142.60	141.23	150	-	117	38	32	3
	64-8M-30F	8F	64	2517	60	162.97	161.60	168	125	-	38	45	7	
	72-8M-30F	8WF	72	2517	60	183.35	181.97	192	125	158	38	45	7	
	80-8M-30F	8W	80	2517	60	203.72	202.35	-	125	180	38	45	7	
	Utan Flänsar Without Flanges	90-8M-30F	8A	90	2517	60	229.18	227.81	-	125	204	38	45	7
	112-8M-30F	8A	112	2517	60	285.21	283.83	-	125	260	38	45	7	
	144-8M-30F	8A	144	2517	60	366.69	365.32	-	125	341	38	45	7	