

MIAB-FIX SPÄNNFÖRBAND


MIAB-FIX CLAMPING UNITS

MIAB-FIX DS-ES															
Best. ex. MIAB-FIX-DS/ES-d								DS				ES			
d	D	D _i	A	B	L	M		T _s	T	F	P	T _s	T	F	P
mm	mm	mm	mm	mm	mm	mm		Nm	Nm	Nm	kN	N/mm²	Nm	kN	N/mm²
20	47	56	22	28	34	M 6		14	410	41	140	17	320	32	100
22	47	56	22	28	34	M 6		14	450	41	140	17	350	32	100
24	50	59	22	28	34	M 6		14	490	41	130	17	390	32	100
25	50	59	22	28	34	M 6		14	510	41	130	17	400	32	100
28	55	64	22	28	34	M 6		14	570	41	120	17	450	32	90
30	55	64	22	28	34	M 6		14	610	41	120	17	490	32	90
32	60	69	22	28	34	M 6		14	880	55	145	17	700	43	110
35	60	69	22	28	34	M 6		14	960	55	145	17	760	43	110
38	65	74	22	28	34	M 6		14	1000	55	135	17	820	43	100
40	65	74	22	28	34	M 6		14	1100	55	135	17	870	43	100
42	75	84	25	33	41	M 8		35	2200	105	190	41	1700	80	140
45	75	84	25	33	41	M 8		35	2400	105	190	41	1800	80	140
48	80	89	24	33	41	M 8		35	2500	105	175	41	1900	80	130
50	80	89	24	33	41	M 8		35	2600	105	175	41	2000	80	130
55	85	91	24	33	41	M 8		35	2900	105	165	41	2200	80	120
60	90	99	24	33	41	M 8		35	3100	105	155	41	2400	80	120
65	95	104	24	33	41	M 8		35	3400	105	150	41	2600	80	110
70	110	119	29	40	50	M 10		70	6000	170	175	83	4600	130	130
75	115	124	29	40	50	M 10		70	6400	170	170	83	5000	130	130
80	120	129	29	40	50	M 10		70	6800	170	160	83	5300	130	120
85	125	134	29	40	50	M 10		70	9000	210	190	83	7000	160	150
90	130	139	29	40	50	M 10		70	9600	210	185	83	7400	160	140
95	135	144	29	40	50	M 10		70	10200	210	185	83	7800	160	130
100	145	154	32	44	56	M 12		115	12000	235	170	145	9700	200	140
110	155	164	32	44	56	M 12		115	13000	260	160	145	10700	200	130
120	165	174	32	44	56	M 12		115	16000	270	165	145	14600	242	150
130	180	189	40	52	64	M 12		115	23000	350	155	145	19000	300	130
140	190	199	40	54	68	M 14		185	25000	360	150	230	23000	330	140
150	200	209	40	54	68	M 14		185	30000	400	155	230	24500	330	130
160	210	219	40	54	68	M 14		-	-	-	-	230	31300	390	150
180	235	244	50	64	78	M 14		-	-	-	-	230	35000	390	100
200	260	269	50	64	78	M 14		-	-	-	-	230	49000	500	110




MIAB-FIX DS (kort)

MIAB-FIX D



MIAB-FIX DS



MIAB-FIX D

MIAB-FIX DS-D

Självcenterande. Stort överförbart moment. Under åtdragningsmomentet kan navet förflytta sig axiellt på grund av att dessa typer ej har en positionsring.

MIAB-FIX DS-D


Self centering without position ring. High transmissible torque. During the clamping the hub can axially displace.

MIAB-FIX D-E															
Best. ex. MIAB-FIX-D/E-d								D				E			
d	D	D _i	A	B	L	M		T _s	T	F	P	T _s	T	F	P
mm	mm	mm	mm	mm	mm	mm		Nm	Nm	Nm	kN	N/mm ²	Nm	kN	N/mm ²
20	47	53	31.0	42	48	M 6		17	530	52	110	17	320	33	70
22	47	53	31.0	42	48	M 6		17	580	52	110	17	360	33	70
24	50	56	31.0	42	48	M 6		17	630	52	100	17	390	33	70
25	50	56	31.0	42	48	M 6		17	660	52	100	17	400	33	70
28	55	61	31.0	42	48	M 6		17	740	52	100	17	450	33	60
30	55	61	31.0	42	48	M 6		17	790	52	100	17	490	33	60
32	60	66	31.0	42	48	M 6		17	1200	70	120	17	690	43	70
35	60	66	31.0	42	48	M 6		17	1300	70	120	17	750	43	70
38	65	71	31.0	42	48	M 6		17	1300	70	110	17	820	43	70
40	65	71	31.0	42	48	M 6		17	1400	70	110	17	860	43	70
42	75	81	36.0	50	58	M 8		41	2000	100	120	41	1300	60	70
45	75	81	36.0	50	58	M 8		41	2200	100	120	41	1400	60	70
48	80	86	36.0	50	58	M 8		41	3200	130	150	41	2000	80	90
50	80	86	36.0	50	58	M 8		41	3300	130	150	41	2000	80	90
55	85	91	36.0	50	58	M 8		41	3600	130	140	41	2200	80	90
60	90	96	36.0	50	58	M 8		41	3900	130	130	41	2400	80	80
65	95	101	36.0	50	58	M 8		41	4300	130	120	41	2600	80	70
70	110	119	46.0	60	70	M 10		83	7500	210	130	83	4600	130	80
75	115	124	46.0	60	70	M 10		83	8000	210	130	83	5000	130	80
80	120	129	46.0	60	70	M 10		83	8500	210	120	83	5200	130	70
85	125	134	46.0	60	70	M 10		83	11400	270	150	83	7000	170	90
90	130	139	46.0	60	70	M 10		83	12000	270	140	83	7400	170	80
100	145	155	52.0	68	80	M 12		145	15000	300	130	145	9800	190	80
110	155	165	52.0	68	80	M 12		145	16500	300	120	145	10700	190	70
120	165	175	52.0	68	80	M 12		145	22500	370	140	145	14600	240	90
130	180	188	52.0	68	80	M 12		145	29000	450	150	145	19000	300	100
140	190	199	58.5	76	90	M 14		210	32000	460	130	230	23000	330	90
150	200	209	58.5	76	90	M 14		210	41000	550	150	230	30000	400	100
160	210	219	58.5	76	90	M 14		210	44000	550	140	230	32000	400	100
170	225	234	58.5	76	90	M 14		210	54500	640	160	230	39000	460	110
180	235	244	58.5	76	90	M 14		210	57500	640	150	230	41000	460	100




MIAB-FIX ES (kort)

MIAB-FIX E



MIAB-FIX ES



MIAB-FIX E

MIAB-FIX ES-E

Självcenterande. Medium överförbart moment. Under åtdragningsmomentet förblir navet axiellt fixerat, då dessa typer har positionsring.

MIAB-FIX ES-E

Self centering without position ring. Medium transmissible torque. During the clamping the hub remains axially fixed.