

PARALLELLKOPPLINGAR

PARALLEL CRANK PRINCIPLES COUPLING

PK-koppling / PK-Coupling heavy serie

Typ / Type NA

Best. Nr. Code	Måttuppgifter i mm. / Dimension in mm																							T stat	J	Vikt/Weight
	A1	A2	A4	A7	B	C	D	G	H	K	L1	L2	L3	L4	L5	M	W	a	a1	a2	b	d	e	Nm	kg m2	kg
280.150.350/4		414	510			272	350	180	115					250									180	31000	9.284	120
280.150.350/5																	80	85.0			22		26	39000	9.913	200
280.150.400/5	280			1)	48					5	150	145	37		270	M20				22	33			46000	15.500	155
280.150.400/6		454	550			320	400							275								200	55000	16.500	165	
280.150.500/6						420	500							325			100	106.4			28			73000	30.385	243

Typ / Type NAS

Best. Nr. Code	Måttuppgifter i mm./Dimension in mm																							T stat	J	Vikt/Weight
	A1	A2	A4	A7	B	C	D	G	H	K	L1	L2	L3	L4	L5	M	W	a	a1	a2	b	d	e	Nm	kg m2	kg
460.230.425/3						300	425							328									200	100000	41.80	380
460.230.480/3																								115000	58.30	425
460.230.480/4						350	480							355								210		150000	60.40	440
460.230.560/4	460	1)	1)	1)	80			1)	1)	1)	230	220	56		414	1)	1)	1)	1)	1)	1)	1)	1)	190000	99.55	550
460.230.560/5						432	560							395								220		238000	105.00	580
460.230.620/6						490	620							425								250		325000	156.80	700
600.320.580/3						400	580							450								220		275000	153.80	800
600.320.700/3	600	1)	1)	1)	100	520	700	1)	1)	1)	320	304	80	510	575	1)	1)	1)	1)	1)	1)	300	1)	355000	275.50	950
600.320.680/4						500	680							500										450000	345.30	1250

Efter montering skall axialspelet tillåtas vara ± 4 mm.

After mounting the axial float shall permitted to be ± 4 mm.

1) Navlängd, diameter och fästhål efter kundspecifikation.

1) Length of nave, diameter and hole an customers request special.