

# KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING, HTD

## TIMING BELT PULLEYS FOR TAPER BUSH, HTD

### HTD 8M-50

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-8M-50F	4F	28	1108	25	71.30	70.08	75	-	50	60	22	19.0
		30-8M-50F	5F	30	1615	42	76.39	75.13	83	-	58	60	38	22.0
		32-8M-50F	5F	32	1615	42	81.49	80.16	87	-	62	60	38	22.0
		34-8M-50F	5F	34	1615	42	86.58	85.22	91	-	65	60	38	22.0
		36-8M-50F	5F	36	1615	42	91.67	90.30	97	-	68	60	38	22.0
		38-8M-50F	5F	38	1615	42	96.77	95.39	102	-	72	60	38	22.0
		40-8M-50F	4F	40	2012	50	101.86	100.49	112	-	82	60	32	14.0
		44-8M-50F	4F	44	2012	50	112.05	110.67	120	-	91	60	32	14.0
		48-8M-50F	4F	48	2012	50	122.23	120.86	128	-	95	60	32	14.0
		56-8M-50F	4F	56	2517	60	142.60	141.23	150	-	116	60	45	7.5
		64-8M-50F	4F	64	2517	60	162.97	161.60	168	-	137	60	45	7.5
		72-8M-50F	9WF	72	2517	60	183.35	181.97	192	125	158	60	45	7.5
	80-8M-50F	4	80	3020	75	203.72	202.35	-	-	180	60	51	4.5	
	90-8M-50F	9W	90	3020	75	229.18	227.81	-	170	204	60	51	4.5	
	112-8M-50F	9W	112	3020	75	285.21	283.83	-	170	260	60	51	4.5	
	Utan Flänsar Without Flanges	144-8M-50F	9A	144	3020	75	366.69	365.52	-	170	341	60	51	4.5
		168-8M-50F	9A	168	3020	75	427.81	426.44	-	170	402	60	51	4.5
		192-8M-50F	9A	192	3020	75	488.92	487.55	-	170	460	60	51	4.5

### HTD 8M-85

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	34-8M-85F	4F	34	1615	42	86.58	85.22	91	-	65	95	38	28.5
		36-8M-85F	4F	36	1615	42	91.67	90.30	97	-	68	95	38	28.5
		38-8M-85F	4F	38	1615	42	96.77	95.39	102	-	72	95	38	28.5
		40-8M-85F	4F	40	2012	50	101.86	100.49	112	-	82	95	32	31.5
		44-8M-85F	4F	44	2012	50	112.05	110.67	120	-	91	95	32	31.5
		48-8M-85F	4F	48	2517	60	122.23	120.86	128	-	100	95	45	25.0
		56-8M-85F	4F	56	2517	60	142.60	141.23	150	-	117	95	45	25.0
		64-8M-85F	4F	64	2517	60	162.97	161.60	168	-	137	95	45	25.0
		72-8M-85F	4F	72	3020	75	183.35	181.97	192	-	158	95	51	22.0
		80-8M-85F	4	80	3020	75	203.72	202.35	-	-	180	95	51	22.0
		90-8M-85F	9W	90	3020	75	229.78	227.81	-	170	204	95	51	22.0
		112-8M-85F	9W	112	3020	75	285.21	283.83	-	170	260	95	51	22.0
	Utan Flänsar Without Flanges	144-8M-85F	9A	144	3030	75	366.69	365.32	-	170	341	95	76	9.5
		168-8M-85F	9A	168	3030	75	427.81	426.44	-	170	402	95	76	9.5
		192-8M-85F	9A	192	3030	75	488.92	487.55	-	170	460	95	76	9.5