

KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING, HTD

TIMING BELT PULLEYS FOR TAPER BUSH, HTD

HTD 14M-85

Utförande Version		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-14M-85F	4F	28	2517	60	124.78	122.12	128	-	98	102	45	28.5
		29-14M-85F	4F	29	2517	60	129.23	126.57	150	-	100	102	45	28.5
		30-14M-85F	4F	30	2517	60	133.69	130.99	150	-	100	102	45	28.5
		32-14M-85F	4F	32	2517	60	142.60	139.88	158	-	108	102	45	28.5
		34-14M-85F	4F	34	2517	60	151.52	148.79	158	-	110	102	45	28.5
		36-14M-85F	4F	36	3020	75	160.43	157.68	168	-	125	102	51	25.5
		38-14M-85F	4F	38	3020	75	169.34	166.60	184	-	130	102	51	25.5
		40-14M-85F	4F	40	3020	75	178.25	175.49	192	-	138	102	51	25.5
		44-14M-85F	4F	44	3030	75	196.08	193.28	211	-	155	102	76	13.0
		48-14M-85F	4F	48	3030	75	213.90	211.11	226	-	170	102	76	13.0
	Utan Flänsar Without Flanges	56-14M-85F	4F	56	3535	90	249.55	246.76	265	190	210	102	89	6.5
		64-14M-85F	9WF	64	3535	90	285.21	282.41	296	190	242	102	89	6.5
		72-14M-85F	9W	72	3535	90	320.86	318.06	-	190	280	102	89	6.5
		80-14M-85F	9A	80	3535	90	356.51	353.71	-	190	315	102	89	6.5
		90-14M-85F	9A	90	3535	90	401.07	398.28	-	190	360	102	89	6.5
		112-14M-85F	9A	112	3535	90	499.11	496.32	-	190	457	102	89	6.5
		144-14M-85F	9A	144	3535	90	641.71	638.92	-	190	600	102	89	6.5
		168-14M-85F	9A	168	3535	90	748.66	745.87	-	190	706	102	89	6.5
		192-14M-85F	3A	192	4040	100	855.62	852.82	-	230	813	102	102	-
		216-14M-85F	3A	216	4040	100	962.57	959.76	-	230	920	102	102	-

HTD 14M-115

Utförande Version		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-14M-115F	4F	28	2517	60	124.78	122.12	128	-	98	133	45	44.0
		29-14M-115F	4F	29	2517	60	129.23	126.57	150	-	100	133	45	44.0
		30-14M-115F	4F	30	2517	60	133.69	130.99	150	-	100	133	45	44.0
		32-14M-115F	4F	32	2517	60	142.60	139.88	158	-	108	133	45	44.0
		34-14M-115F	4F	34	2517	60	151.52	148.79	158	-	110	133	45	44.0
		36-14M-115F	4F	36	3020	75	160.43	157.68	168	-	125	133	51	41.0
		38-14M-115F	4F	38	3020	75	169.34	166.60	184	-	130	133	51	41.0
		40-14M-115F	4F	40	3020	75	178.25	175.49	192	-	140	133	51	41.0
		44-14M-115F	4F	44	3030	75	196.08	193.28	211	-	155	133	76	28.5
		48-14M-115F	4F	48	3030	75	213.90	211.11	226	-	170	133	76	28.5
	Utan Flänsar Without Flanges	56-14M-115F	4F	56	3535	90	249.55	246.76	265	-	210	133	89	22.0
		64-14M-115F	9WF	64	3535	90	285.21	282.41	296	190	242	133	89	22.0
		72-14M-115F	9W	72	3535	90	320.86	318.06	-	190	280	133	89	22.0
		80-14M-115F	9A	80	3535	90	356.51	353.71	-	190	315	133	89	22.0
		90-14M-115F	9A	90	3535	90	401.07	398.28	-	190	360	133	89	22.0
		112-14M-115F	9A	112	3535	90	499.11	496.32	-	190	457	133	89	22.0
		144-14M-115F	9A	144	4040	100	641.71	638.92	-	230	600	133	102	15.5
		168-14M-115F	9A	168	4040	100	748.66	745.87	-	230	706	133	102	15.5
		192-14M-115F	9A	192	4040	100	855.62	852.82	-	230	813	133	102	15.5
		216-14M-115F	9A	216	4040	100	962.57	959.76	-	230	920	133	102	15.5

HTD 14M-170

Utförande Features		Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	38-14M-170F	4F	38	3030	75	169.34	166.60	184	-	130	187	76	55.5
		40-14M-170F	4F	40	3030	75	178.25	175.49	192	-	140	187	76	55.5
		44-14M-170F	4F	44	3535	90	196.08	193.28	211	-	155	187	89	49.0
		48-14M-170F	4F	48	3535	90	213.90	211.11	226	-	175	187	89	49.0
		56-14M-170F	4F	56	3535	90	249.55	246.76	265	-	210	187	89	49.0
		64-14M-170F	4F	64	4040	100	285.21	282.41	296	-	240	187	102	42.5
	Utan Flänsar Without Flanges	72-14M-170F	9W	72	4040	100	320.86	318.06	-	230	280	187	102	42.5
		80-14M-170F	9W	80	4040	100	356.51	353.71	-	230	315	187	102	42.5
		90-14M-170F	9A	90	4040	100	401.07	398.28	-	230	360	187	102	42.5
		112-14M-170F	9A	112	5050	125	499.11	496.32	-	265	456	187	127	30.0
		144-14M-170F	9A	144	5050	125	641.71	638.92	-	265	600	187	127	30.0
		168-14M-170F	9A	168	5050	125	748.66	745.87	-	265	706	187	127	30.0
		192-14M-170F	9A	192	5050	125	855.62	852.82	-	265	813	187	127	30.0
		216-14M-170F	9A	216	5050	125	962.57	959.76	-	265	920	187	127	30.0