


# KUGGREMOR FÖR HTD, PROFIL 3M, 5M, 8M, 14M, 20M

TIMING BELT FOR HTD, PROFILE 3M, 5M, 8M, 14M, 20M

Material: Neoprengummi med glasfiberkord.  
Kuggar förstärkta med nylonväv.

Material: Neopren rubber with glasfiberkord.  
Nylon fabric on the tooth surface.



## 3M

Längd mm Length mm	Antal tänder No. of teeth
111	37
117	39
129	43
141	47
144	48
150	50
156	52
159	53
168	56
174	58
177	59
180	60
186	62
192	64
201	67
204	68
210	70
213	71
216	72
225	75
240	80
246	82
252	84
255	85
285	95
294	98
300	100
312	104
318	106
336	112
339	113
363	121
384	128
390	130
420	140
447	149
474	158
480	160
486	162
495	165

## 3M

Längd mm Length mm	Antal tänder No. of teeth
501	167
513	171
522	174
525	175
531	177
537	179
564	188
570	190
597	199
600	200
606	202
612	204
633	211
669	223
708	236
711	237
738	246
753	251
822	274
843	281
882	294
945	315
1041	347
1068	356
1071	357
1125	375
1176	392
1245	415
1263	421
1500	500
1530	510
1569	523

P	3.00
H	2.40
H1	1.17

## 5M

Längd mm Length mm	Antal tänder No. of teeth
225	45
265	53
275	55
295	59
300	60
330	66
350	70
375	75
400	80
425	85
450	90
460	92
475	95
500	100
525	105
535	107
550	110
565	113
580	116
600	120
615	123
620	124
665	133
700	140
710	142
740	148
755	151
800	160
835	167
890	178
900	180
925	185
950	190
1000	200
1050	210
1125	225
1270	254
1420	284
1500	300
1595	319
1790	358
1800	360
1870	374
2000	400
2525	505

P	5.0
H	3.40
H1	2.06

## 8M

Längd mm Length mm	Antal tänder No. of teeth
376	47
424	53
472	59
480	60
560	70
600	75
624	78
640	80
656	82
720	90
776	97
784	98
800	100
880	110
912	114
920	115
960	120
1040	130
1120	140
1200	150
1280	160
1304	163
1328	166
1360	170
1424	175
1440	180
1600	200
1760	220
1800	225
2000	250
2248	281
2400	300
2800	350

P	8.00
H	6.00
H1	3.40

## 14M

Längd mm Length mm	Antal tänder No. of teeth
966	69
1190	85
1400	100
1610	115
1778	127
1890	135
2100	150
2310	165
2450	175
2590	185
2800	200
3150	225
3500	250
3850	275
4326	309
4578	327

P	14.00
H	10.00
H1	6.10

## 20M

Längd mm Length mm	Antal tänder No. of teeth
2000	100
3400	170
4200	210
5000	250
5400	270
5800	290
6200	310

P	20.0
H	13.2
H1	8.4

### Standard bredder / Standard widths

- Typ 3M / Type 3M: 6 mm, 9 mm, 15 mm
- Typ 5M / Type 5M: 9 mm, 15 mm, 25 mm
- Typ 8M / Type 8M: 20 mm, 30 mm, 50 mm, 85 mm
- Typ 14M / Type 14M: 40 mm, 55 mm, 85 mm, 115 mm, 170 mm
- Typ 20M / Type 20M: 115 mm, 170 mm, 200 mm, 290 mm, 340 mm