


# INNERKUGGKRANSAR

## INTERNAL GEAR

Material: Stål C45  
Material: Steel C45

Ingreppsvinkel 20°  
Pressure angle 20°



### MODUL 1.0

| Best. Nr.<br>Code | Antal tänder Z<br>No. of teeth Z | do    | di    | D   | b |
|-------------------|----------------------------------|-------|-------|-----|---|
| SI10025           | 25                               | 25    | 23.0  | 50  | 8 |
| SI10030           | 30                               | 30    | 28.0  | 55  | 8 |
| SI10032           | 32                               | 32    | 30.0  | 60  | 8 |
| SI10036           | 36                               | 36    | 34.0  | 60  | 8 |
| SI10040           | 40                               | 40    | 38.0  | 65  | 8 |
| SI10045           | 45                               | 45    | 43.0  | 70  | 8 |
| SI10048           | 48                               | 48    | 46.0  | 75  | 8 |
| SI10050           | 50                               | 50    | 48.0  | 75  | 8 |
| SI10055           | 55                               | 55    | 53.0  | 80  | 8 |
| SI10060           | 60                               | 60    | 58.0  | 85  | 8 |
| SI10065           | 65                               | 65    | 63.0  | 90  | 8 |
| SI10070           | 70                               | 70    | 68.0  | 95  | 8 |
| SI10072           | 72                               | 72    | 70.0  | 100 | 8 |
| SI10080           | 80                               | 80    | 78.0  | 105 | 8 |
| SI10090           | 90                               | 90    | 88.0  | 115 | 8 |
| SI10100           | 100                              | 100.0 | 98.0  | 125 | 8 |
| SI10120           | 120                              | 120.0 | 118.0 | 150 | 8 |

### MODUL 1.5

| Best. Nr.<br>Code | Antal tänder Z<br>No. of teeth Z | do    | di    | D   | b  |
|-------------------|----------------------------------|-------|-------|-----|----|
| SI10525           | 25                               | 37.5  | 34.5  | 70  | 12 |
| SI10530           | 30                               | 45.0  | 42.0  | 75  | 12 |
| SI10532           | 32                               | 48.0  | 45.0  | 80  | 12 |
| SI10536           | 36                               | 54.0  | 51.0  | 85  | 12 |
| SI10540           | 40                               | 60.0  | 57.0  | 90  | 12 |
| SI10545           | 45                               | 67.5  | 64.5  | 100 | 12 |
| SI10548           | 48                               | 72.0  | 69.0  | 100 | 12 |
| SI10550           | 50                               | 75.0  | 72.0  | 105 | 12 |
| SI10555           | 55                               | 82.5  | 79.5  | 112 | 12 |
| SI10560           | 60                               | 90.0  | 87.0  | 120 | 12 |
| SI10565           | 65                               | 97.5  | 94.5  | 120 | 12 |
| SI10570           | 70                               | 105.0 | 102.0 | 135 | 12 |
| SI10572           | 72                               | 108.0 | 105.0 | 140 | 12 |
| SI10580           | 80                               | 120.0 | 117.0 | 150 | 12 |
| SI10590           | 90                               | 135.0 | 132.0 | 170 | 12 |
| SI105100          | 100                              | 150.0 | 147.0 | 190 | 12 |
| SI105120          | 120                              | 180.0 | 177.0 | 220 | 12 |

### MODUL 2.0

| Best. Nr.<br>Code | Antal tänder Z<br>No. of teeth Z | do    | di    | D   | b  |
|-------------------|----------------------------------|-------|-------|-----|----|
| SI20030           | 30                               | 60.0  | 56.0  | 95  | 16 |
| SI20036           | 36                               | 72.0  | 68.0  | 107 | 16 |
| SI20040           | 40                               | 80.0  | 76.0  | 115 | 16 |
| SI20045           | 45                               | 90.0  | 86.0  | 125 | 16 |
| SI20048           | 48                               | 96.0  | 92.0  | 131 | 16 |
| SI20050           | 50                               | 100.0 | 96.0  | 135 | 16 |
| SI20055           | 55                               | 110.0 | 106.0 | 145 | 16 |
| SI20060           | 60                               | 120.0 | 116.0 | 155 | 16 |
| SI20065           | 65                               | 130.0 | 126.0 | 165 | 16 |
| SI20070           | 70                               | 140.0 | 136.0 | 175 | 16 |
| SI20072           | 72                               | 144.0 | 140.0 | 185 | 16 |
| SI20080           | 80                               | 160.0 | 156.0 | 195 | 16 |
| SI20090           | 90                               | 180.0 | 176.0 | 220 | 16 |
| SI20100           | 100                              | 200.0 | 196.0 | 240 | 16 |