

TEKNISK INFO, PROFIL HTD
TECHNICAL INFORMATION, PROFILE HTD

Effekttabell för profil 20M / *Power table profile 20M*

Varvtal n1 <i>R.P.M. n1</i>	Tandantal lilla hjulet / No. of teeth small pulley													
	34	36	38	40	44	48	52	56	60	64	68	72	80	90
10	2.0	2.1	2.3	2.4	2.6	2.9	3.2	3.4	3.6	3.8	4.0	4.1	4.5	4.9
20	4.0	4.3	4.5	4.8	5.4	5.8	6.3	6.8	7.2	7.6	7.9	8.3	9.1	9.9
30	6.0	6.4	6.8	7.2	8.0	8.8	9.5	10.2	10.8	11.3	11.9	12.4	13.5	14.9
40	7.9	8.5	9.1	9.6	10.7	11.6	12.6	13.6	14.4	15.2	15.9	16.6	18.0	19.8
50	9.9	10.6	11.3	12.0	13.3	14.6	15.8	17.0	18.0	18.9	19.9	20.8	22.6	24.7
60	11.8	12.7	13.5	10.7	16.0	17.4	18.9	20.4	21.6	22.7	23.8	25.0	27.1	29.7
80	15.8	17.0	18.0	19.2	21.3	23.3	25.2	27.2	28.8	30.2	31.7	33.2	36.1	39.5
100	19.7	21.2	22.6	24.0	26.7	29.1	31.5	33.9	35.9	37.8	39.7	41.5	45.1	49.4
150	29.7	31.8	33.9	36.0	40.0	43.6	47.3	50.9	53.9	56.7	59.5	62.2	67.6	74.0
200	39.5	42.4	45.1	48.0	53.3	58.1	63.0	67.8	71.7	75.4	79.1	82.8	89.9	98.3
300	57.2	61.5	65.3	69.4	77.9	86.6	92.3	97.8	103.3	108.6	113.7	118.8	128.7	140.4
400	72.1	77.3	82.1	87.2	97.7	108.6	115.4	122.1	128.7	135.0	141.2	147.2	158.8	172.4
500	85.9	92.0	97.7	103.7	116.0	128.7	136.5	144.2	151.6	158.8	165.7	172.4	185.2	199.8
600	98.8	105.8	112.2	119.1	132.9	147.2	156.0	164.3	172.4	180.2	187.6	194.7	207.9	222.6
730	114.6	122.5	129.8	137.6	151.8	169.3	178.8	187.8	196.4	204.5	212.1	219.3	232.1	245.2
800	122.6	131.1	138.7	146.8	163.3	180.2	190.0	199.2	207.9	216.0	223.5	230.4	242.4	253.9
870	130.3	139.2	147.2	155.7	173.0	190.5	200.5	209.8	218.4	226.3	233.6	240.1	250.9	260.1
970	140.7	150.1	158.6	167.7	185.8	204.1	214.2	223.3	231.6	239.1	245.6	251.2	259.2	-
1170	159.7	170.0	179.1	188.9	208.0	227.4	236.8	244.9	251.7	257.1	261.1	263.5	263.9	-
1200	162.4	172.7	182.0	191.7	211.2	230.4	239.6	247.5	253.9	258.9	262.3	264.2	252.9	-
1460	183.0	193.9	203.4	213.4	232.8	251.6	258.0	262.4	264.4	263.9	260.9	-	-	-
1600	192.3	203.4	212.7	222.5	241.3	258.9	263.1	264.4	262.9	-	-	-	-	-
1750	200.9	211.8	220.8	230.1	247.7	263.4	264.2	261.8	-	-	-	-	-	-
2000	212.0	222.1	230.0	238.0	251.9	262.9	-	-	-	-	-	-	-	-

Angivet värde i kW / tum / *Values per 1" width in kW*

Rembreddsfaktor / *Belt width factor*

Rembredd / <i>Belt width</i>	115	170	230 (>38 denti)	290 (>52 denti)	340 (>52 denti)
Faktor / <i>Factor</i>	1.00	1.55	2.15	2.80	3.26