

# FLÄNSLAGER, FYRKANTIGT UTFÖRANDE

## SQUARE FLANGE UNITS

### UCF 2 • UCF 3


(låsnings med stoppskruv)  
(set screw locking)

### EFW 2 • EFW 3



(låsnings med excentrisk låsring)  
(eccentric locking collar)

Axelhål 12-140mm

Shaft dia. 12-140mm



UCF



EFW

Best. nr. Code	Axelhål Shaft dia.	Mått i mm / Dimensions in mm											Bult st. Bolt size	Vikt Weight kg
		L	J	A	A <sub>1</sub>	A <sub>2</sub>	N	B	B <sub>1</sub>	S	A <sub>6</sub>	H <sub>a</sub>		
UCF 201	12	86	64	25.5	12	15	12	31.0	-	12.7	33.3	-	M 10	0.67
UCF 202	15	86	64	25.5	12	15	12	31.0	-	12.7	33.3	-	M 10	0.66
UCF 203	17	86	64	25.5	12	15	12	31.0	-	12.7	33.3	-	M 10	0.64
UCF 204	20	86	64	25.5	12	15	12	31.0	-	12.7	33.3	-	M 10	0.62
EFW 204	20	86	64	25.5	12	15	12	-	43.7	17.1	41.6	33	M 10	0.68
UCF 205	25	95	70	27.0	14	16	12	34.0	-	14.3	35.7	-	M 10	0.83
EFW 205	25	95	70	27.0	14	16	12	-	44.4	17.5	42.9	39	M 10	0.86
UCF 305	25	110	80	29.0	13	16	16	38.0	-	15.0	39.0	-	M 14	1.14
EFW 305	25	110	80	29.0	13	18	16	-	46.8	16.7	46.1	41	M 14	1.21
UCF 206	30	108	83	31.0	14	18	12	38.1	-	15.9	40.2	-	M 10	1.14
EFW 206	30	108	83	31.0	14	18	12	-	48.4	18.3	48.1	45	M 10	1.19
UCF 306	30	125	95	32.0	15	18	16	43.0	-	17.0	44.0	-	M 14	1.64
EFW 306	30	125	95	32.0	15	18	16	-	50.0	17.5	50.5	-	M 14	1.75
UCF 207	35	117	92	34.0	16	19	14	42.9	-	17.5	44.4	-	M 12	1.47
EFW 207	35	117	92	34.0	16	19	14	-	51.1	18.8	51.3	52	M 12	1.60
UCF 307	35	135	100	36.0	16	20	19	48.0	-	19.0	49.0	-	M 16	2.20
EFW 307	35	135	100	36.0	16	20	19	-	51.6	18.3	53.3	-	M 16	2.30
UCF 208	40	130	102	36.0	16	21	16	49.2	-	19.0	51.2	-	M 14	2.00
EFW 208	40	130	102	36.0	16	21	16	-	56.3	21.4	55.9	57	M 14	2.10
UCF 308	40	150	112	40.0	17	23	19	52.0	-	19.0	56.0	-	M 16	2.90
EFW 308	40	150	112	40.0	17	23	19	-	57.1	19.8	60.3	-	M 16	3.10
UCF 209	45	137	105	38.0	18	22	16	49.2	-	19.0	52.2	-	M 14	2.40
EFW 209	45	137	105	38.0	18	22	16	-	56.3	21.4	56.9	62	M 14	2.50
UCF 309	45	160	125	44.0	18	25	19	57.0	-	22.0	60.0	-	M 16	3.60
EFW 309	45	160	125	44.0	18	25	19	-	58.7	19.8	63.9	-	M 16	3.70
UCF 210	50	143	111	40.0	18	22	16	51.6	-	19.0	54.6	-	M 14	2.60
EFW 210	50	143	111	40.0	18	22	16	-	62.7	24.6	60.1	67	M 14	2.70
UCF 310	50	175	132	48.0	19	28	23	61.0	-	22.0	67.0	-	M 20	4.70
EFW 310	50	175	132	48.0	19	28	23	-	66.6	24.6	70.0	-	M 20	4.90
UCF 211	55	162	130	43.0	20	25	19	55.6	-	22.2	58.4	-	M 16	3.6
EFW 211	55	162	130	43.0	20	25	19	-	71.4	27.8	68.6	75	M 16	3.80
UCF 311	55	185	140	52.0	20	30	23	66.0	-	25.0	71.0	-	M 20	5.80
EFW 311	55	185	140	52.0	20	30	23	-	73.0	27.8	75.2	-	M 20	6.00
UCF 212	60	175	143	48.0	20	29	19	65.1	-	25.4	68.7	-	M 16	4.80
EFW 212	60	175	143	48.0	20	29	19	-	77.8	31.0	75.8	83	M 16	5.00
UCF 312	60	195	150	56.0	22	33	23	71.0	-	26.0	78.0	-	M 20	7.40
EFW 312	60	195	150	56.0	22	33	23	-	79.4	31.0	81.4	-	M 20	7.80
UCF 213	65	187	149	50.0	20	30	19	65.1	-	25.4	69.7	-	M 16	5.80
EFW 213	65	187	149	50.0	20	30	19	-	85.7	34.1	81.6	89	M 16	6.30
UCF 313	65	208	166	58.0	22	33	23	75.0	-	30.0	78.0	-	M 16	8.30
EFW 313	65	208	166	58.0	22	33	23	-	85.7	32.5	86.2	-	M 20	8.90
UCF 214	70	193	152	54.0	24	31	19	74.6	-	30.2	75.4	-	M 16	6.60
EFW 214	70	193	152	54.0	24	31	19	-	85.7	34.1	81.6	93	M 16	7.10
UCF 314	70	226	178	61.0	25	36	25	78.0	-	33.0	81.0	-	M 22	9.80
EFW 314	70	226	178	61.0	25	36	25	-	92.1	34.1	94.0	-	M 22	10.50
UCF 215	75	200	159	56.0	24	34	19	77.8	-	33.3	78.5	-	M 16	7.70
EFW 215	75	200	159	56.0	24	34	19	-	92.1	37.3	88.8	100	M 16	8.10
UCF 315	75	236	184	66.0	25	39	25	82.0	-	32.0	89.0	-	M 22	11.20
EFW 315	75	236	184	66.0	25	39	25	-	100.0	37.3	101.7	-	M 22	12.40