


KILREMSSKIVOR FÖR KONISK KLÄMBUSSNING

V-BELT PULLEYS FOR TAPER BUSH


Profil A/SPA
Profile A/SPA




Utf. / Type 1




Utf. / Type 2




Utf. / Type 3




Utf. / Type 4



Utf. / Type 5



Utf. / Type 6



Utf. / Type 9

Do	Ant. spår Grooves	Buss. Nr. Bush No.	Best. Nr. Code	Max A-hål Max bore	Typ	B	J	K	L	M	N	Vikt Weight
63	1	1108	1SPA63	28	9	20	31	18.0	40.0	-	68.5	0.6
	2	1108	2SPA63	28	9	35	31	33.0	55.0	-	68.5	0.8
67	1	1108	1SPA67	28	1	20	-	-	22.0	2.0	60.0	0.3
	2	1108	2SPA67	28	3	35	35	13.0	22.0	-	-	0.5
71	1	1108	1SPA71	28	1	20	-	-	22.0	2.0	60.0	0.3
	2	1108	2SPA71	28	3	35	39	13.0	22.0	-	-	0.5
	3	1108	3SPA71	28	3	50	39	28.0	22.0	-	-	0.7
75	1	1108	1SPA75	28	1	20	-	-	22.0	2.0	60.0	0.4
	2	1108	2SPA75	28	3	35	43	13.0	22.0	-	-	0.6
	3	1108	3SPA75	28	3	50	43	28.0	22.0	-	-	0.8
80	1	1210	1SPA80	32	1	20	-	-	25.0	5.0	80.0	0.5
	2	1210	2SPA80	32	3	35	50	10.0	25.0	-	-	0.6
	3	1210	3SPA80	32	3	50	50	25.0	25.0	-	-	0.9
85	1	1210	1SPA85	32	1	20	-	-	25.0	5.0	80.0	0.6
	2	1210	2SPA85	32	3	35	55	10.0	25.0	-	-	0.7
	3	1210	3SPA85	32	3	50	55	25.0	25.0	-	-	1.0
90	1	1210	1SPA90	32	1	20	-	-	25.0	5.0	80.0	0.7
	2	1610	2SPA90	42	3	35	60	10.0	25.0	-	-	0.7
	3	1610	3SPA90	42	3	50	60	23.5	26.5	-	-	1.0
	4	1610	4SPA90	42	3	65	60	40.0	25.0	-	-	1.2
95	1	1210	1SPA95	32	1	20	-	-	25.0	5.0	80.0	0.8
	2	1610	2SPA95	42	3	35	65	10.0	25.0	-	-	0.9
	3	1610	3SPA95	42	3	50	65	23.5	26.5	-	-	1.1
	4	1610	4SPA95	42	3	65	65	40.0	25.0	-	-	1.4
100	1	1610	1SPA100	42	1	20	-	-	25.0	5.0	92.0	0.8
	2	1610	2SPA100	42	3	35	65	10.0	25.0	-	-	0.9
	3	1610	3SPA100	42	2	50	65	-	25.0	25	-	1.2
	4	1610	4SPA100	42	2	65	65	-	25.0	40	-	1.7
	5	1610	5SPA100	42	3	80	65	55.0	25.0	-	-	1.9
	6	1610	6SPA100	42	4	95	65	30.0	25.0	40.0	-	2.3
106	1	1610	1SPA106	42	1	20	-	-	25.0	5.0	92.0	0.9
	2	1610	2SPA106	42	3	35	70	10.0	25.0	-	-	1.1
	3	1610	3SPA106	42	2	50	70	-	25.0	25.0	-	1.4
	4	2012	4SPA106	50	3	65	70	33.0	32.0	-	-	2.0
	5	2012	5SPA106	50	3	80	70	48.0	32.0	-	-	2.0
	6	2012	6SPA106	50	3	95	70	63.0	32.0	-	-	2.4
112	1	1610	1SPA112	42	1	20	-	-	25.0	5.0	92.0	1.0
	2	1610	2SPA112	42	3	35	77	10.0	25.0	-	-	1.2
	3	2012	3SPA112	50	3	50	77	18.0	32.0	-	-	1.3
	4	2012	4SPA112	50	3	65	77	33.0	32.0	-	-	1.9
	5	2012	5SPA112	50	3	80	77	48.0	32.0	-	-	2.1
	6	2012	6SPA112	50	3	95	77	63.0	32.0	-	-	2.4
118	1	1610	1SPA118	42	1	20	-	-	25.0	5.0	85.0	1.2
	2	1610	2SPA118	42	3	35	84	10.0	25.0	-	-	1.4
	3	2012	3SPA118	50	2	50	84	-	32.0	18.0	-	1.8
	4	2012	4SPA118	50	2	65	84	-	32.0	33.0	-	2.0
	5	2012	5SPA118	50	2	80	84	-	32.0	48.0	-	2.4
	6	2012	6SPA118	50	3	95	84	63.0	32.0	-	-	2.7
125	1	1610	1SPA125	42	1	20	-	-	25.0	5.0	92.0	1.4
	2	1610	2SPA125	42	2	35	90	-	25.0	10.0	-	1.7
	3	2012	3SPA125	50	2	50	90	-	32.0	18.0	-	2.0
	4	2012	4SPA125	50	2	65	90	-	32.0	33.0	-	2.5
	5	2012	5SPA125	50	2	80	90	-	32.0	48.0	-	2.7
	6	2012	6SPA125	50	4	95	90	31.5	32.0	31.5	-	3.0

Do	Ant. spår Grooves	Buss. Nr. Bush No.	Best. Nr. Code	Max A-hål Max bore	Typ	B	J	K	L	M	N	Vikt Weight
132	1	1610	1SPA132	42	1	20	-	-	26.5	6.5	92	1.6
	2	2012	2SPA132	50	2	35	98	-	32	3.0	-	1.8
	3	2012	3SPA132	50	2	50	98	-	32	18.0	-	2.3
	4	2517	4SPA132	65	2	65	98	-	45	20.0	-	2.6
	5	2517	5SPA132	65	2	80	98	-	45	35.0	-	2.9
	6	2517	6SPA132	65	4	95	98	25.0	45	25.0	-	3.3
140	1	1610	1SPA140	42	1	20	-	-	25	5.0	92	1.8
	2	2012	2SPA140	50	2	35	105	-	32	3.0	-	2.0
	3	2012	3SPA140	65	2	50	105	-	45	5.0	-	2.8
	4	2517	4SPA140	65	2	65	105	-	45	20.0	-	3.1
	5	2517	5SPA140	65	2	80	105	-	45	35.0	-	3.4
	6	2517	6SPA140	65	4	95	105	25.0	45	25.0	-	3.8
150	1	1610	1SPA150	42	1	20	-	-	25	5.0	92	1.4
	2	2012	2SPA150	50	2	35	115	-	32	3.0	-	2.4
	3	2517	3SPA150	65	2	50	115	-	45	5.0	-	3.5
	4	2517	4SPA150	65	2	65	115	-	45	20.0	-	3.8
	5	2517	5SPA150	65	2	80	115	-	45	35.0	-	4.2
	6	2517	6SPA150	65	4	95	115	25.0	45	25.0	-	4.8
160	1	1610	1SPA160	42	5	20	125	-	25	5.0	92	1.9
	2	2012	2SPA160	50	2	35	125	-	32	3.0	-	2.9
	3	2517	3SPA160	65	2	50	125	-	45	5.0	-	3.9
	4	2517	4SPA160	65	2	65	125	-	45	20.0	-	4.4
	5	2517	5SPA160	65	2	80	125	-	45	35.0	-	5.1
	6	2517	6SPA160	65	4	95	125	25.0	45	25.0	-	5.8
170	1	1610	1SPA170	42	5	20	135	-	25	5.0	92	2.0
	2	2012	2SPA170	50	2	35	135	-	32	3.0	-	3.1
	3	2517	3SPA170	65	2	50	135	-	45	5.0	-	4.6
	4	2517	4SPA170	65	2	65	135	-	45	20.0	-	5.5
	5	3020	5SPA170	75	2	80	135	-	51	29.0	-	5.9
	6	3020	6SPA170	75	4	95	135	22.0	51	22.0	-	6.5
180	1	1610	1SPA180	42	5	20	145	-	25	5.0	92	2.1
	2	2012	2SPA180	50	6	35	145	-	32	3.0	110	3.4
	3	2517	3SPA180	65	2	50	145	-	45	5.0	-	5.1
	4	2517	4SPA180	65	2	65	145	-	45	20.0	-	5.9
	5	3020	5SPA180	75	2	80	145	-	51	29.0	-	6.2
	6	3020	6SPA180	75	4	95	145	22.0	51	22.0	-	6.7
190	1	1610	1SPA190	42	5	20	155	-	25	5.0	92	2.3
	2	2012	2SPA190	55	6	35	155	-	32	3.0	110	3.8
	3	2517	3SPA190	65	2	50	155	-	45	5.0	-	5.4
	4	2517	4SPA190	65	2	65	155	-	45	20.0	-	6.8
	5	3020	5SPA190	75	2	80	155	-	51	29.0	-	7.4
	6	3020	6SPA190	75	4	95	155	22.0	51	22.0	-	8.1
200	1	2012	1SPA200	50	5	20	165	-	32	12.0	112	2.6
	2	2517	2SPA200	65	5	35	165	-	45	10.0	124	4.1
	3	2517	3SPA200	65	6	50	165	-	45	5.0	124	4.9
	4	3020	4SPA200	75	2	65	165	-	51	14.0	-	7.4
	5	3020	5SPA200	75	4	80	165	14.5	51	14.5	-	8.4
	6	3020	6SPA200	75	4	95	165	22.0	51	22.0	-	9.4
212	1	2012	1SPA212	50	5	20	177	-	32	12.0	112	2.7
	2	2517	2SPA212	65	5	35	177	-	45	10.0	124	4.3
	3	2517	3SPA212	65	6	50	177	-	45	5.0	124	5.2
	4	3020	4SPA212	75	2	65	177	-	51	14.0	-	7.3
	5	3020	5SPA212	75	2	80	177	-	51	29.0	-	8.2
	6	3020	6SPA212	75	4	95	177	22.0	51	22.0	-	9.2